

LED line PRIME

Code: 203754

EAN: 5905378203754

LINKER TRI-PROOF 40W 4000K 6000lm  
150lm/W 220-240V IP65 120cm black  
PRIME



The LINKER 40W colour temperature 4000K emits a light stream of 6000 lumens, which translates into a high light performance of 150 lm/W. Thanks to the IP65 class, it is fully protected from dust and water, allowing it to be used in difficult conditions. High overall durability, exceeding 100000 hours of operation and impact resistance IK08 make the frame characterized by reliability and long-term operation.



Technical data

| Parameter                         | Value          |
|-----------------------------------|----------------|
| Energy efficiency class 2019/2015 | C              |
| Energy class                      | A+             |
| Warranty                          | 5              |
| Power                             | • 40 W         |
| Voltage                           | • 220-240 V AC |
| Correlated colour temperature     | • 4000 K       |
| Colour of the light               | White          |
| Colour rendering index Ra         | 80             |
| IP protection rating              | IP65           |
| IK protection rating              | 08             |
| IEC protection class              | II             |
| Luminous efficacy                 | 150            |
| Luminous flux                     | 6000           |
| The lumen maintenance factor      | 96             |
| Lifetime L70B50                   | 100 000 h      |

| Parameter                                  | Value         |
|--------------------------------------------|---------------|
| Survival factor                            | 0,9           |
| Colour consistency in McAdam ellipses      | ≤6            |
| Frequency of the supply voltage            | 50/60Hz       |
| Beam angle                                 | 120           |
| LED type                                   | SMD2835       |
| Lifespan                                   | 100 000 h     |
| Number of on/off cycles                    | 50000         |
| Lamp's warm-up time to 60%                 | 1 s           |
| Ambient temperature suitable for operation | -25÷45        |
| Length                                     | 1180          |
| Width                                      | 72            |
| Height                                     | 61            |
| Colour                                     | Grey          |
| Material (housing)                         | Polycarbonate |
| Material (cover)                           | polycarbonate |


LED line PRIME

Code: 203754


EAN: 5905378203754

LINKER TRI-PROOF 40W 4000K 6000lm  
150lm/W 220-240V IP65 120cm black  
PRIME

Technical drawing




Light distribution



Additional product photos




Logistics data




Single packaging

|        |         |
|--------|---------|
| Width  | 1180 mm |
| Height | 61 mm   |
| Length | 72 mm   |
| Weight | 1,13 kg |



Bulk packaging

|          |          |
|----------|----------|
| Quantity | 15       |
| Width    | 355 mm   |
| Height   | 246 mm   |
| Length   | 1238 mm  |
| Volume   | 0,108 m3 |
| Weight   | 17,3 kg  |



Europallet

|                   |          |
|-------------------|----------|
| Quantity          | 150      |
| Height            | 1775 mm  |
| Quantity in layer | 135      |
| Number of layers  | 1        |
| Bulk quantity     | 135      |
| Weight            | 778,5 kg |

---

LED line PRIME

Code: 203754

EAN: 5905378203754

**LINKER TRI-PROOF 40W 4000K 6000lm  
150lm/W 220-240V IP65 120cm black  
PRIME**

---

**Example application**