

LED line PRIME

Code: 211285

EAN: 5905378211285

**Module Rialto 70AS 4000K 1.8W PRIME**



Rialto 70AS 4000K 1.8W PRIME is a modern light source that provides excellent energy efficiency and light efficiency of 63 lm/W. The user can enjoy a white light with a temperature of 4000 K, which favors comfortable illumination of the space. Made of aluminum, it is characterized by durability and aesthetic appearance. The wide angle of illumination of 70° asymmetric makes it ideal for spreading light in the desired direction.



**Technical data**

Parameter	Value
Energy efficiency class 2019/2015	G
Warranty	5
Power	• 1.8 W
Voltage	• 24 V DC
Correlated colour temperature	• 4000 K
Colour of the light	White
Colour rendering index Ra	80
IP protection rating	IP67
Luminous efficacy	63
Luminous flux	113
The lumen maintenance factor	96
Lifetime L70B50	50 000 h

Parameter	Value
Survival factor	0.9
Dimmable function	PWM
Colour consistency in McAdam ellipses	≤6
Beam angle	70 Asymmetric
LED quantity	1
Not dimmable	TAK
Number of on/off cycles	50000
Lamp's warm-up time to 60%	1 s
Ambient temperature suitable for operation	-20 ÷ 45
Width	∅ 33 / ∅ 37
Height	40
Material (housing)	Aluminium


LED line PRIME

Code: 211285

EAN: 5905378211285


**Module Rialto 70AS 4000K 1.8W PRIME**

**Technical drawing**






**Light distribution**

**Additional product photos**



**Logistics data**



**Single packaging**

Quantity	1
Width	250 mm
Height	230 mm
Length	350 mm
Weight	0,02 kg
Comments	

**Bulk packaging**

Quantity	180
Width	370 mm
Height	260 mm
Length	520 mm
Volume	0,5 m <sup>3</sup>
Weight	21,8 kg
Comments	

**Europallet**

Quantity	240
Height	1800 mm
Quantity in layer	4
Number of layers	6
Bulk quantity	24
Weight	192 kg

---

LED line PRIME

Code: 211285

EAN: 5905378211285

**Module Rialto 70AS 4000K 1.8W PRIME**

---

**Example application**