

LED line LITE


Code: 211605

EAN: 5905378211605

LED line LITE LINIX 120cm 36W 4000K 4320lm IP65



LINIX 36W 4000K 4320lm IP65 LITE from LED line LITE is a modern lighting solution, characterized by high light performance of 4320 lumens. At 36 W power consumption and 220-240 V AC power supply, the product achieves an excellent PF power factor of 0.95. Thanks to the IP65 class of tightness and IK07 strength, the housing is resistant to adverse weather and mechanical conditions.



Technical data

Parameter	Value
Energy efficiency class 2019/2015	E
Power	• 36 W
Voltage	• 220-240 V AC
Correlated colour temperature	• 4000 K
Colour of the light	White
Colour rendering index Ra	80
IEC protection class	II
Luminous efficacy	120
Luminous flux	4320
The lumen maintenance factor	96
Survival factor	0,9
Colour consistency in McAdam ellipses	≤6
Mounting type	mixed

Parameter	Value
Frequency of the supply voltage	50/60Hz
CRI colour rendering index	80
Beam angle	120
Lifespan	20 000 h
Power Factor	0,95
Lamp's warm-up time to 60%	1 s
Ambient temperature suitable for operation	-20÷40
Length	1237
Width	53
Height	27
Material (housing)	Polycarbonate
Material (cover)	polystyrene

LED line LITE


Code: 211605

EAN: 5905378211605


LED line LITE LINIX 120cm 36W 4000K

4320lm IP65

Technical drawing



Light distribution



Additional product photos



Logistics data




Single packaging

Width	51 mm
Height	25 mm
Length	1275 mm
Weight	0,301 kg



Bulk packaging

Width	275 mm
Height	190 mm
Length	1280 mm
Weight	9,9 kg



Europallet

Bulk quantity	480
Weight	160 kg

LED line LITE

Code: 211605

EAN: 5905378211605

**LED line LITE LINIX 120cm 36W 4000K
4320lm IP65**

Example application