

LED line PRIME

Code: 218574

EAN: 5905378218574

**Ceiling Light LEDIS 3CCT(3K/4K/6K)
12/16W 1600lm round IP65 white PRIME**



LEDIS ceiling with adjustable power of 12/16W by LED line **PRIME** is an excellent solution for lighting outdoor and indoor spaces. The choice of color temperature in the ranges **3000 K, 4000 K, and 6000 K** allows for adaptation to the character of the surroundings.



Technical data

Parameter	Value
Energy efficiency class 2019/2015	D
Warranty	5
Power	<ul style="list-style-type: none"> • 12 W • 16 W
Voltage	<ul style="list-style-type: none"> • 220-240 V AC
Correlated colour temperature	<ul style="list-style-type: none"> • 3000 K • 4000 K • 6000 K
Colour of the light	White
Colour rendering index Ra	80
IP protection rating	IP65
IK protection rating	08
IEC protection class	II
Luminous efficacy	100
Luminous flux	1600
The lumen maintenance factor	96
Lifetime L70B50	35 000 h
Survival factor	0.9
Colour consistency in McAdam ellipses	≤6
Output current	0,073

Parameter	Value
Frequency of the supply voltage	50/60Hz
Beam angle	120
LED type	SMD2835
LED quantity	182
Lifespan	35 000 h
Power Factor	0,5
Number of on/off cycles	50000
Lamp's warm-up time to 60%	1
Ambient temperature suitable for operation	-40÷35
Installation method	surface
Height	85
Fixture's diameter	320
Weight	0,86 kg
Colour	White
Material (housing)	Polycarbonate
Material (cover)	Polycarbonate


LED line PRIME

Code: 218574


EAN: 5905378218574

**Ceiling Light LEDIS 3CCT(3K/4K/6K)
12/16W 1600lm round IP65 white PRIME**

Technical drawing



Light distribution



Additional product photos



Logistics data



Single packaging

Quantity	1
Width	320 mm
Height	320 mm
Length	85 mm
Weight	1,1 kg

Bulk packaging

Quantity	6
Width	700 mm
Height	320 mm
Length	320 mm
Volume	
Weight	6,7 kg
Comments	

Europallet

Quantity	72
Height	1,6 m
Quantity in layer	
Number of layers	
Bulk quantity	12
Weight	110 kg

LED line PRIME

Code: 218574

EAN: 5905378218574

**Ceiling Light LEDIS 3CCT(3K/4K/6K)
12/16W 1600lm round IP65 white PRIME**

Example application