

LED line PRIME


Code: 207134

EAN: 5905378207134

Park luminaire Nolina 60W 4000K
9000lm black PRIME



The 60W Nolina Park luminaire and a light stream of 9000 lm is characterized by high light efficiency of 150 lm/W, which allows considerable energy savings. Made of durable materials, including aluminium casting and polycarbonate block, provides resistance to atmospheric conditions (IP66) and mechanical damage (IK08).



Technical data

Parameter	Value
Energy efficiency class 2019/2015	C
Warranty	5
Power	• 60 W
Voltage	• 220-240 V AC
Correlated colour temperature	• 4000 K
Colour of the light	White
Colour rendering index Ra	70
IP protection rating	IP66
IK protection rating	08
IEC protection class	I
Luminous efficacy	150
Luminous flux	9000
The lumen maintenance factor	96
Lifetime L70B50	70 000 h
Survival factor	0.9
Colour consistency in McAdam ellipses	≤6

Parameter	Value
Wire length	550 mm
Frequency of the supply voltage	50/60Hz
Fixture's diameter	450
Beam angle	100
LED type	SMD LED
Power Factor	0,95
Number of on/off cycles	50000
Lamp's warm-up time to 60%	1 s
Ambient temperature suitable for operation	-40+50
Width	450
Height	577
Weight	6000
Colour	Black
Material (housing)	Die cast aluminium
Material (cover)	polycarbonate

LED line PRIME

Code: 207134


EAN: 5905378207134

Park luminaire Nolina 60W 4000K
9000lm black PRIME




Technical drawing

Light distribution

Additional product photos



Logistics data



Single packaging

Quantity	1
Width	485 mm
Height	635 mm
Length	485 mm
Weight	7,87 kg

Bulk packaging

Quantity	1
Width	470 mm
Height	430 mm
Length	450 mm
Volume	0,09 m3
Weight	7,7 kg

Europallet

LED line PRIME

Code: 207134

EAN: 5905378207134

**Park luminaire Nolina 60W 4000K
9000lm black PRIME**

Example application