

LED line PRIME

Code: 217539

EAN: 5905378217539


**Solar park light SUNLO 2CCT (3/4K)
2200lm IP65 black PRIME**



SUNLO is an innovative solar luminaire that combines elegant, **modern** design with advanced technology. Thanks to the use of an A-class monocrystalline solar panel, it ensures the highest solar energy conversion efficiency.

The **SUNLO** luminaire offers two operating **modes: full power 100%** (lighting from dusk to dawn) and **eco mode 50%**, which extends operating time and reduces energy consumption.

Additionally, it allows adjustment of the color temperature in the range of **3000 K** (warm) or **4000 K** (neutral). This allows for precise adaptation of the lighting character to the surroundings and individual user preferences.



Technical data

| Parameter | Value |
|-------------------------------|------------------------|
| Warranty | 5 |
| Power | • 20 W |
| Correlated colour temperature | • 3000 K • 4000 K |
| Colour of the light | White |
| Colour rendering index Ra | 80 |
| IP protection rating | IP65 |
| IEC protection class | III |
| Luminous flux | 2200 |
| Lifetime L70B50 | 35 000 h |
| Loading time | 6 h |
| Photo cell power | 12,5 W |
| Photo cell voltage | 10 V |
| Photo cell current | 1,25 A |
| Mounting type | Lighting pole ø 60mm |
| Type of battery | LiFe PO4 6.4V 6000 mAh |

| Parameter | Value |
|--|---------------|
| Beam angle | 120 |
| Motion detection range and angle | 120 |
| LED type | SMD 2835 |
| LED quantity | 64 |
| Lamp's warm-up time to 60% | 1 |
| Ambient temperature suitable for operation | -20 +50 |
| For indoor use | Outside |
| Height | 120 mm |
| Fixture's diameter | 400 mm |
| Diameter | 400 mm |
| Weight | 2,7 kg |
| Battery life | 32 h |
| Colour | black |
| Material (housing) | ABS |
| Material (cover) | Polycarbonate |

LED line PRIME

Code: 217539

EAN: 5905378217539

**Solar park light SUNLO 2CCT (3/4K)
2200lm IP65 black PRIME**



Technical drawing

Light distribution

Additional product photos



Logistics data



Single packaging

| | |
|----------|--------|
| Quantity | 1 |
| Width | 150 mm |
| Height | 430 mm |
| Length | 430 mm |
| Weight | 3,4 kg |

Bulk packaging

| | |
|----------|---|
| Quantity | 1 |
|----------|---|

Europallet

| | |
|-------------------|--------|
| Quantity | 48 |
| Quantity in layer | |
| Number of layers | |
| Bulk quantity | 48 |
| Weight | 200 kg |

LED line PRIME

Code: 217539

EAN: 5905378217539

**Solar park light SUNLO 2CCT (3/4K)
2200lm IP65 black PRIME**

Example application

