

LED line PRIME

Code: 203044

EAN: 5905378203044

LED line PRIME Floodlight 150W CCT 21000lm 90°



The PRIME Floodlight 150W LED line reflector is an excellent lighting solution with high power and light stream of 21000 lumens. It is characterized by a 90° light angle, which provides effective space illumination. Made of aluminum and tempered glass, it guarantees durability and resistance to atmospheric conditions, reaching IP66 protection class.



Technical data

Parameter	Value
Energy efficiency class 2019/2015	D
Warranty	5
Power	• 150 W
Voltage	• 100-277 V AC
Correlated colour temperature	• 3000 K • 4000 K • 5000 K
Colour of the light	CCT
Colour rendering index Ra	70
IP protection rating	IP66
IK protection rating	08
IEC protection class	I
Luminous efficacy	140
Luminous flux	21000
The lumen maintenance factor	96
Lifetime L70B50	50 000 h
L80B* – difference B10–B50 ≈ 1% (according to LightingEurope) – negligible	35000 h
Survival factor	0.9

Parameter	Value
Colour consistency in McAdam ellipses	≤6
Mounting type	surface
Frequency of the supply voltage	50/60Hz
Beam angle	90
LED type	SMD2835
LED quantity	360
Power Factor	0,9
Number of on/off cycles	50000
Lamp's warm-up time to 60%	1
Ambient temperature suitable for operation	-40÷45
Length	412
Width	360
Height	54
Weight	3,3
Material (housing)	Aluminium
Material (cover)	Tempered glass

LED line PRIME

Code: 203044

EAN: 5905378203044

LED line PRIME Floodlight 150W CCT 21000lm 90°




Technical drawing

Light distribution

Additional product photos



Logistics data



Single packaging

Width	420 mm
Height	80 mm
Length	450 mm
Weight	5,5 kg

Bulk packaging

Quantity	1
Width	42 mm
Height	80 mm
Length	450 mm
Volume	0,0151 m3
Weight	5,5 kg
Comments	

Europallet

Quantity	60
Height	1260 mm
Quantity in layer	20
Number of layers	3
Bulk quantity	60
Weight	330 kg

LED line PRIME

Code: 203044

EAN: 5905378203044

**LED line PRIME Floodlight 150W CCT
21000lm 90°**

Example application