

LED line

Code: 248849

EAN: 5901583248849

LED line Panel Easy Fix 24W 4000K
2300lm round



LED panel Easy Fix 24W 4000K 2300lm from LED line is an advanced lighting solution that emits neutral light, perfectly reflective colors thanks to the Ra indicator at level 80. Its high light performance of 96 lm/W at a 2300 lumen luminous flux provides optimal brightness. The product is characterized by a minimalist design and durable housing with polyamide and polystyrene tin.

3
WARRANTY

IP
20

IK
05

220-260V
AC

PF
0,5

MAX
-5÷40°C

CE

Technical data

Parameter	Value
Energy efficiency class 2019/2015	E
Energy class	A++
Warranty	3
Power	• 24 W
Voltage	• 220-260 V AC
Correlated colour temperature	• 4000 K
Colour of the light	White
Colour rendering index Ra	80
IP protection rating	IP20
IEC protection class	II
Luminous efficacy	96
Luminous flux	2300
The lumen maintenance factor	96
Lifetime L70B50	30 000 h
Survival factor	0.9
Colour consistency in McAdam ellipses	≤6

Parameter	Value
Frequency of the supply voltage	50/60Hz
Fixture's diameter	290 mm
Beam angle	120
LGP	PMMA
LED type	SMD2835
LED quantity	112
Power Factor	0,7
Number of on/off cycles	50000
Lamp's warm-up time to 60%	1
Ambient temperature suitable for operation	-5÷40
For indoor use	Inside
Mounting hole diameter	60-260
Height	13
Colour	white
Material (housing)	Polyamide
Material (cover)	Polystyrene


LED line

Code: 248849


EAN: 5901583248849

LED line Panel Easy Fix 24W 4000K
2300lm round

Technical drawing




Light distribution



Additional product photos




Logistics data




Single packaging

Quantity	1
Width	313 mm
Height	40 mm
Length	296 mm
Weight	0,76 kg



Bulk packaging

Quantity	10
Width	320 mm
Height	315 mm
Length	430 mm
Volume	0,043 m3
Weight	10 kg
Comments	



Europallet

Quantity	180
Height	1890 mm
Quantity in layer	40
Number of layers	6
Bulk quantity	240
Weight	268,8 kg

LED line

Code: 248849

EAN: 5901583248849

**LED line Panel Easy Fix 24W 4000K
2300lm round**

Example application