

LED line LITE

Code: 475534

EAN: 5907777475534

## LED line LITE Outdoor wall mounted luminaire LED 2x3W 3000K IP54 gray CILINDER



The CILINDER 2x3W outdoor wall is a modern lighting setting that combines elegance with functionality. Thanks to two independent light sources, it is possible to adjust the lighting angle from 0 to 120 degrees. The product is durable, providing IP54 protection and impressive light performance of 490 lumens with only 6 W consumption.



### Technical data

Parameter	Value
Energy efficiency class 2019/2015	G
Warranty	3
Power	• 6 W
Voltage	• 100-260 V AC
Correlated colour temperature	• 3000 K
Colour of the light	White
Colour rendering index Ra	80
IP protection rating	IP54
IK protection rating	05
IEC protection class	II
The lumen maintenance factor	96
Lifetime L70B50	30 000 h
Survival factor	0.9

Parameter	Value
Colour consistency in McAdam ellipses	≤6
Frequency of the supply voltage	50/60Hz
Beam angle	0-120
LED type	2835 SMD
LED quantity	14
Power Factor	0,5
Number of on/off cycles	20000
Ambient temperature suitable for operation	-20÷40
Length	13,5
Width	11,5
Height	10
Material (housing)	Aluminium
Material (cover)	glass

LED line LITE


Code: 475534

EAN: 5907777475534

LED line LITE Outdoor wall mounted luminaire LED 2x3W 3000K IP54 gray CILINDER

Technical drawing




Light distribution



Additional product photos



Logistics data



Single packaging

Quantity	1
Width	110 mm
Height	110 mm
Length	110 mm
Weight	0,35 kg

Bulk packaging

Quantity	40
Width	460 mm
Height	310 mm
Length	640 mm
Volume	0,091 m3
Weight	14,35 kg
Comments	

Europallet

Quantity	840
Height	1840 mm
Quantity in layer	120
Number of layers	4
Bulk quantity	480
Weight	172,2 kg

---

LED line LITE

Code: 475534

EAN: 5907777475534

**LED line LITE Outdoor wall mounted  
luminaire LED 2x3W 3000K IP54 gray  
CILINDER**

---

**Example application**