

LED line PRIME

Code: 200180-DALI

EAN: 5905378218666

LED line PRIME Panel Backlit 40W  
4000K 4800lm 595x595



Backlit panel 40W 4000K 4800lm 60x60 DALI PRIME from LED line PRIME is an advanced lighting solution with high performance. By emitting a light stream of 4,800 lumens at only 40 watts, the panel provides excellent energy efficiency at class E level. Thanks to the colour of the light 4000 K, it is ideal for different interior applications.



Technical data

Parameter	Value
Energy efficiency class 2019/2015	E
Energy class	A+
Warranty	5
Power	• 40 W
Voltage	• 220-240 V AC
Correlated colour temperature	• 4000 K
Colour of the light	White
Colour rendering index Ra	80
IP protection rating	IP20
IK protection rating	02
IEC protection class	II
Luminous efficacy	120
Luminous flux	4800
The lumen maintenance factor	96
Lifetime L70B50	75 000 h

Parameter	Value
Survival factor	0.9
Colour consistency in McAdam ellipses	≤6
Frequency of the supply voltage	50/60Hz
Beam angle	120
LED type	SMD LED 2835
LED quantity	48
Power Factor	0,9
Number of on/off cycles	25000
Lamp's warm-up time to 60%	1 s
Ambient temperature suitable for operation	-25÷45
For indoor use	Inside
Height	28
Colour	white
Material (housing)	Aluminium
Material (cover)	polystyrene

LED line PRIME

Code: 200180-DALI


EAN: 5905378218666

LED line PRIME Panel Backlit 40W

4000K 4800lm 595x595

Technical drawing


Light distribution



Additional product photos




Logistics data




Single packaging

Quantity	1
Width	30 mm
Height	640 mm
Length	600 mm
Weight	1,41 kg



Bulk packaging

Quantity	5
Width	170 mm
Height	655 mm
Length	615 mm
Volume	0,075 m3
Weight	9,6 kg
Comments	



Europallet

Quantity	60
Height	1880 mm
Quantity in layer	25
Number of layers	2
Bulk quantity	60
Weight	132 kg

LED line PRIME

Code: 200180-DALI

EAN: 5905378218666

**LED line PRIME Panel Backlit 40W  
4000K 4800lm 595x595**

**Example application**

