

LED line LITE

Code: 209879-II

EAN: 5905378227576

**Downlight MOLLY 3CCT(3K/4K/6K) 24W
2150lm round IP20 black LITE**



The black LED panel Molly 3CCT combines ultra-slim minimalist design with an elegant dark finish, perfect for modern loft arrangements. The fixture offers a color temperature change function (3000K/4000K/6000K) in one device, allowing for instant adjustment of lighting to the user's needs. Thanks to its universal design, the product is suitable for both recessed and surface mounting, ensuring style and flexibility in every investment.

IP
20

Technical data

Parameter	Value
Energy efficiency class 2019/2015	F
Warranty	3
Power	• 24 W
Voltage	• 220-240 V AC
Correlated colour temperature	• 3000-4000-6000 K
Colour of the light	CCT
Colour rendering index Ra	80
IP protection rating	IP20
IK protection rating	05
IEC protection class	II
Luminous efficacy	90

Parameter	Value
Luminous flux	2150
Lifetime L70B50	25 000 h
Frequency of the supply voltage	50/60Hz
Beam angle	120°
Power Factor	0,7
Ambient temperature suitable for operation	-20÷40
For indoor use	Inside
Height	26 mm
Fixture's diameter	225 mm
Weight	0,276 kg
Material (housing)	Polycarbonate


LED line LITE

Code: 209879-II

EAN: 5905378227576

**Downlight MOLLY 3CCT(3K/4K/6K) 24W
2150lm round IP20 black LITE**

Technical drawing



Light distribution

Additional product photos




Logistics data



Single packaging

Width	230 mm
Height	40 mm
Length	230 mm
Weight	0,343 kg



Bulk packaging

Quantity	20
Width	48 cm
Height	43 cm
Length	25 cm
Weight	7,36 kg



Europallet

Quantity	280
Height	1,8 m
Bulk quantity	14
Weight	140 kg

LED line LITE

Code: 209879-II

EAN: 5905378227576

**Downlight MOLLY 3CCT(3K/4K/6K) 24W
2150lm round IP20 black LITE**

Example application