

LED line PRIME

Code: 200302

EAN: 5905378200302

**FLOODLIGHT 4000K 50W 7000lm 60°
IP66 PRIME**



The PRIME Floodlight 50W LED line light provides exceptional lighting with 140 lm/W efficiency and a light stream of 7000 lm. The technology used SMD2835 guarantees long-term, reliable operation and IP66 leak class and IK08 resistance provide excellent resistance to difficult weather conditions. High light quality with a colour temperature of 4000 K promotes uniform dispersion and precise light management.



Technical data

Parameter	Value
Energy efficiency class 2019/2015	D
Warranty	5/7*
Power	• 50 W
Voltage	• 100-277 V AC
Correlated colour temperature	• 4000 K
Colour of the light	White
Colour rendering index Ra	70
IP protection rating	IP66
IK protection rating	08
IEC protection class	I
Luminous efficacy	140
Luminous flux	7000
The lumen maintenance factor	96
Lifetime L70B50	50 000 h
L80B* – difference B10–B50 ≈ 1% (according to LightingEurope) – negligible	35000 h
Survival factor	0.9
Colour consistency in McAdam ellipses	≤6

Parameter	Value
Wire length	920 mm
Mounting type	surface
Frequency of the supply voltage	50/60Hz
Beam angle	60
LED type	SMD2835
LED quantity	96
Power Factor	0,9
Number of on/off cycles	50000
Lamp's warm-up time to 60%	1
Ambient temperature suitable for operation	-40÷45
Length	243 mm
Width	214 mm
Height	42 mm
Weight	1
Material (housing)	Aluminium
Material (cover)	Tempered glass

LED line PRIME

Code: 200302


EAN: 5905378200302

**FLOODLIGHT 4000K 50W 7000lm 60°
IP66 PRIME**

Technical drawing





Light distribution



Additional product photos



Logistics data



Single packaging

Width	252 mm
Height	43,5 mm
Length	213 mm
Weight	1 kg

Bulk packaging

Quantity	10
Width	480 mm
Height	285 mm
Length	320 mm
Volume	0,043 m3
Weight	10,35 kg
Comments	

Europallet

Quantity	200
Height	1710 mm
Quantity in layer	40
Number of layers	6
Bulk quantity	240
Weight	248,4 kg

LED line PRIME

Code: 200302

EAN: 5905378200302

**FLOODLIGHT 4000K 50W 7000lm 60°
IP66 PRIME**

Example application