

LED line LITE


Code: 211612

EAN: 5905378211612

LED line LITE LINIX 150cm 45W 4000K  
5400lm IP65

New

LINIX 45W 4000K 5400lm is a modern light source with high performance, offering a 5400 lumen light stream. Equipped with LED technology, it is characterized by low power consumption of 45 W and a PF power factor of 0.95. The power supply range is 220 to 240 V AC. The housing is resistant to atmospheric conditions with IP65 leak class and has high mechanical strength IK07.



Technical data

Parameter	Value
Power	• 45 W
Voltage	• 220-240 V AC
Correlated colour temperature	• 4000 K
Luminous efficacy	120
Luminous flux	5400
Lifetime L70B50	20 000 h
Survival factor	0,9

Parameter	Value
Standby power	0
Beam angle	120
Ambient temperature suitable for operation	-20/+40
Length	1574
Width	53
Height	27
Colour	White

LED line LITE


Code: 211612

EAN: 5905378211612

LED line LITE LINIX 150cm 45W 4000K  
5400lm IP65

Technical drawing


Light distribution



Additional product photos




Logistics data




Single packaging

Width	51 mm
Height	25 mm
Length	1575 mm
Weight	0,363 kg



Bulk packaging

Width	275 mm
Height	190 mm
Length	1580 mm
Weight	11,9 kg
Comments	



Europallet

Bulk quantity	480
Weight	190,5 kg

---

LED line LITE

Code: 211612

EAN: 5905378211612

**LED line LITE LINIX 150cm 45W 4000K  
5400lm IP65**

---

**Example application**