

LED line LITE

Code: 470737

EAN: 5907777470737

LED line SMD 5W 4000K 400lm 220-260V 50mm DIM



The modern LED light bulb SMD 5W 4000K from LED line LITE is an impressive light source that emits a 400 lumen light stream with a low energy consumption of only 5 W. It is characterized by a neutral colour of light (4000 K) and a wide light angle of 110°, which allows perfect space lighting. The life of the lamp is as much as 30,000 hours, and the light stream retention rate is 96%.



Technical data

Parameter	Value
Energy efficiency class 2019/2015	G
Energy class	A+
Warranty	3
Power	• 5 W
Voltage	• 220-260 V AC
Correlated colour temperature	• 4000 K
Colour of the light	White
Colour rendering index Ra	80
IEC protection class	II
Luminous efficacy	80
Luminous flux	400
The lumen maintenance factor	96
Lifetime L70B50	30 000 h
Survival factor	0.9
Dimmable function	Triac

Parameter	Value
Colour consistency in McAdam ellipses	≤6
Frequency of the supply voltage	50/60Hz
Fixture's diameter	50 mm
Beam angle	110
LED type	SMD2835
Compatible dimmer type	TRIAC
Power Factor	0,4
Number of on/off cycles	50000
Ambient temperature suitable for operation	-5÷40
For indoor use	Inside
Height	22
Colour	White
Material (housing)	Ceramics
Material (cover)	glass

LED line LITE

Code: 470737


EAN: 5907777470737

LED line SMD 5W 4000K 400lm 220-260V 50mm DIM


Technical drawing





Light distribution



Additional product photos



Logistics data



Single packaging

Quantity	10
Width	50 mm
Height	50 mm
Length	60 mm
Weight	0,08 kg

Bulk packaging

Quantity	100
Width	290 mm
Height	170 mm
Length	595 mm
Volume	0,029 m3
Weight	7 kg
Comments	

Europallet

Quantity	4500
Height	1870 mm
Quantity in layer	400
Number of layers	11
Bulk quantity	4400
Weight	308 kg

---

LED line LITE

Code: 470737

EAN: 5907777470737

**LED line SMD 5W 4000K 400lm 220-  
260V 50mm DIM**

---

**Example application**