

LED line PRIME

Code: 203709

EAN: 5905378203709

LINKER TRI-PROOF 30W 4000K 4500lm
150lm/W 220-240V IP65 120cm PRIME



LINKER 30W 4000K from PRIME LED line is an advanced lighting solution, characterized by high light efficiency of 150 lm/W and 4500 lumen light stream. Thanks to IP65 tightness class, the housing is dust and water resistant, allowing it to be used in difficult conditions. Made of durable polycarbonate and meeting IK08 standards, it is a solid choice for demanding environments.



Technical data

Parameter	Value
Energy efficiency class 2019/2015	D
Energy class	A+
Warranty	5
Power	• 30 W
Voltage	• 220-240 V AC
Correlated colour temperature	• 4000 K
Colour of the light	White
Colour rendering index Ra	80
IP protection rating	IP65
IK protection rating	08
IEC protection class	II
Luminous efficacy	150
Luminous flux	4500
The lumen maintenance factor	96
Lifetime L70B50	100 000 h

Parameter	Value
Survival factor	0.9
Colour consistency in McAdam ellipses	≤6
Frequency of the supply voltage	50/60Hz
Beam angle	120
LED type	SMD2835
Lifespan	100 000 h
Number of on/off cycles	50000
Lamp's warm-up time to 60%	1 s
Ambient temperature suitable for operation	-25÷45
Length	1180
Width	72
Height	61
Material (housing)	Polycarbonate
Material (cover)	polycarbonate

LED line PRIME


Code: 203709

EAN: 5905378203709


LINKER TRI-PROOF 30W 4000K 4500lm

150lm/W 220-240V IP65 120cm PRIME

Technical drawing




Light distribution



Additional product photos




Logistics data




Single packaging

Width	1180 mm
Height	61 mm
Length	72 mm
Weight	1,43 kg



Bulk packaging

Quantity	15
Width	288 mm
Height	246 mm
Length	1538 mm
Volume	0,108 m3
Weight	17,51 kg



Europallet

Quantity	180
Height	1728 mm
Quantity in layer	180
Number of layers	1
Bulk quantity	180
Weight	1260,72 kg

LED line PRIME

Code: 203709

EAN: 5905378203709

**LINKER TRI-PROOF 30W 4000K 4500lm
150lm/W 220-240V IP65 120cm PRIME**

Example application

