

LED line LITE Code: 475541 EAN: 5907777475541

# LED line LITE Outdoor wall mounted luminaire LED 2x3W 4000K IP54 black CILINDER





can be adapted to individual needs.

















#### **Technical data**

Parameter	Value
Energy efficiency class 2019/2015	G
Warranty	3
Power	• 6W
Voltage	• 100-260 V AC
Correlated colour temperature	• 4000 K
Colour of the light	White
Colour rendering index Ra	80
IP protection rating	IP54
IK protection rating	05
IEC protection class	II
The lumen maintenance factor	96
Lifetime L70B50	30 000 h
Survival factor	0.9

Parameter	Value
Colour consistency in McAdam ellipses	<b>≤</b> 6
Frequency of the supply voltage	50/60Hz
Beam angle	0-120
LED type	2835 SMD
LED quantity	14
Power Factor	0,5
Number of on/off cycles	20000
Ambient temperature suitable for operation	-20÷40
Length	13,5
Width	11,5
Height	10
Material (housing)	Aluminium
Material (cover)	glass

lighting solution and 4000K colour temperature, which combines elegance with functionality. It has a degree of protection IP54, which guarantees resistance to water and dust. Thanks to the adjustable lighting angle from 0 to 120 degrees, the light stream



LED line LITE Code: 475541 EAN: 5907777475541

## LED line LITE Outdoor wall mounted luminaire LED 2x3W 4000K IP54 black CILINDER

#### **Technical drawing**

#### Light distribution



#### Additional product photos












#### Logistics data









#### Single packaging

Quantity	1
Width	110 mm
Height	110 mm
Length	110 mm
Weight	0,35 kg

#### Bulk packaging

Quantity	40
Width	460 mm
Height	310 mm
Length	640 mm
Volume	0,091 m3
Weight	14,35 kg
Comments	

#### Europallet

Quantity	840
Height	1840 mm
Quantity in layer	120
Number of layers	4
Bulk quantity	480
Weight	172,2 kg

# MORE EFFICIENCY FOR THE LED WORLD



LED line LITE Code: 475541 EAN: 5907777475541

## LED line LITE Outdoor wall mounted luminaire LED 2x3W 4000K IP54 black CILINDER

**Example application**