

LED line PRIME

Code: 249259

EAN: 5901583249259

LED line downlight round adjustable die cast aluminium black



The PRIME mobile LED line ceiling housing is characterized by modern design and production from aluminium casting, which ensures its durability and aesthetics. It can be installed in different interiors thanks to the possibility to adjust the lighting angle to 45°. IP20 leak class guarantees safety of use, and a 5-year warranty proves high quality. The black and matt finishes perfectly fit the arrangement trends.



Technical data

Parameter	Value
Warranty	5
IP protection rating	IP20
IEC protection class	III
Maximum suitable lamp power	35 W
Fixture's diameter	92
Lamp's diameter	50 mm
Y-axis angle regulation	45

Parameter	Value
Type of surface suitable for installation	F
Distance from illuminated surface	0.5 m
Installation method	recessed
Mounting hole diameter	80
Height	30
Colour	black
Material (housing)	Die cast aluminium


LED line PRIME

Code: 249259

EAN: 5901583249259

LED line downlight round adjustable die cast aluminium black




Technical drawing



Light distribution

Additional product photos

Logistics data



Single packaging

Quantity	1
Width	66 mm
Height	66 mm
Length	42 mm
Weight	0,06 kg

Bulk packaging

Quantity	100
Width	380 mm
Height	220 mm
Length	470 mm
Volume	0,039 m3
Weight	9 kg
Comments	

Europallet

Quantity	2800
Height	1760 mm
Quantity in layer	400
Number of layers	8
Bulk quantity	3200
Weight	288 kg

LED line PRIME

Code: 249259

EAN: 5901583249259

**LED line downlight round adjustable die
cast aluminium black**

Example application