LEDline

LED line PRIME   Code: 205819-AW3HAT   EAN: 5905378216617

Backlit 34W 4000K 4760lm 60x60 emergency module 3h autotest PRIME

203457-01-pic.png

dd36ae3f9bae776071e7088f7fd4f16734743b19.svg

The backlit LED panel with 34W power and 4000K light colour provides a high luminous flux of 4760 lm. Made of aluminium and polystyrene, it is characterized by a low rate of flickering, which affects comfort of use. Energy class C and Ra colour reproduction factor at level 80 guarantee the efficiency and quality of lighting. The panel is equipped with an emergency module running up to 3 hours with autotest function.

icon_CE.svg

Technical data

Parameter	Value		Parameter	Value
Energy efficiency class 2019/2015	C		Colour consistency in McAdam ellipses	≤6
Warranty	5		Emergency module test	autotest
Power	• 34 W		Operating time in emergency mode	3 h
Voltage	• 220-240 V AC		Frequency of the supply voltage	50/60Hz
			Beam angle	90
Correlated colour temperature	• 4000K		LED type	SMD LED 2835
Colour of the light	White		LED quantity	128
Colour rendering index Ra	80		Power Factor	0,9
IP protection rating	IP20		Number of on/off cycles	50000
IK protection rating	02		Lamp's warm-up time to 60%	1 s
IEC protection class	II		Ambient temperature suitable for operation	-20÷40
Luminous efficacy	140		For indoor use	Inside
Luminous flux	4760		Height	30
The lumen maintenance factor	96		Colour	White
Lifetime L70B50	50 000 h		Material (housing)	Aluminium
Survival factor	0.9		Material (cover)	polystyrene
Dimmable function	Triac			

LEDline

LED line PRIME   Code: 205819-AW3HAT   EAN: 5905378216617

Backlit 34W 4000K 4760lm 60x60 emergency module 3h autotest PRIME

Technical drawing   **Light distribution**

**Additional product photos**

Logistics data

Single packaging

Quantity	1
Width	605 mm
Height	32 mm
Length	642 mm
Weight	1,94 kg

Bulk packaging

Quantity	5
Width	
Height	
Length	
Volume	
Weight	
Comments	

Europallet

Backlit 34W 4000K 4760lm 60x60
emergency module 3h autotest PRIME

Example application