

LED line PRIME


Code: 203129

EAN: 5905378203129

LED line PRIME Road luminaire CAMINO
150W 4000K 21000lm



The CAMINO 150W LED line PRIME is an advanced device with high light efficiency of 140 lm/W and a total light stream of 21,000 lm. With a neutral colour of light 4000 K and LUMILEDS diodes, it provides long-lasting performance. IP66 leak class allows for use in difficult weather conditions.



Technical data

Parameter	Value
Energy efficiency class 2019/2015	D
Warranty	5
Power	• 150 W
Correlated colour temperature	• 4000 K
Colour of the light	White
Colour rendering index Ra	70
IP protection rating	IP66
IK protection rating	08
IEC protection class	I
Luminous efficacy	140
Luminous flux	21000
The lumen maintenance factor	96
Lifetime L70B50	100 000 h
Survival factor	0.9

Parameter	Value
Colour consistency in McAdam ellipses	≤6
ULOR	0 %
Frequency of the supply voltage	50/60Hz
Beam angle	150 x 110
LED type	LUMILEDS 2835
LED quantity	240
Power Factor	0,9
Lamp's warm-up time to 60%	1 s
Ambient temperature suitable for operation	-40÷50
Length	634
Width	240
Height	84
Material (housing)	Die cast aluminium
Material (cover)	tempered glass

LED line PRIME


Code: 203129

EAN: 5905378203129


LED line PRIME Road luminaire CAMINO
150W 4000K 21000lm

Technical drawing




Light distribution



Additional product photos



Logistics data



Single packaging

Width	634 mm
Height	84 mm
Length	240 mm
Weight	3,4 kg

Bulk packaging

Quantity	1
Width	2760 mm
Height	1160 mm
Length	6860 mm
Volume	21,96 m3
Weight	3,4 kg

Europallet

Height	1920 mm
Number of layers	1
Bulk quantity	64
Weight	287,4 kg

LED line PRIME

Code: 203129

EAN: 5905378203129

**LED line PRIME Road luminaire CAMINO
150W 4000K 21000lm**

Example application