

LED line LITE

Code: 228917

EAN: 5905378228917



Floodlight PHOTON S 3CCT (3/4/6,5K)
20W 2000lm 120° IP66 LITE



New



PHOTON S is a professional floodlight for buildings, halls, and open areas. The aluminum housing, tempered glass, and pressure equalization system ensure IP66 and IK08. Efficient LEDs 100 lm/W, tool-free installation, 3 light colors, a lumen output of 1,000–30,000 lm, and a PIR option guarantee savings and versatile applications.



Technical data

Parameter	Value
Energy efficiency class 2019/2015	F
Warranty	3
Power	20 W
Voltage	185-265 V AC
Correlated colour temperature	3000 K 4000 K 6500 K
Colour of the light	CCT
Colour rendering index Ra	80
IP protection rating	IP66
IK protection rating	06
IEC protection class	I
Luminous efficacy	100
Luminous flux	2000

Parameter	Value
Lifetime L70B50	30 000 h
Frequency of the supply voltage	50/60Hz
Beam angle	120°
LED type	2835 18V
Power Factor	>=0,9
Ambient temperature suitable for operation	-20÷45
Length	129 mm
Width	90 mm
Height	27 mm
Weight	0,29 kg
Material (housing)	Aluminium

LED line LITE


Code: 228917

EAN: 5905378228917

Floodlight PHOTON S 3CCT (3/4/6,5K)

20W 2000lm 120° IP66 LITE


Technical drawing



Light distribution


Additional product photos

Logistics data




Single packaging

Width	125 mm
Height	35 mm
Length	155 mm
Weight	0,33 kg



Bulk packaging

Quantity	20
Width	265 mm
Height	195 mm
Length	325 mm
Weight	7 kg



Europallet

Quantity	1600
Height	1,7 m
Bulk quantity	80
Weight	600 kg

LED line LITE

Code: 228917

EAN: 5905378228917

Floodlight PHOTON S 3CCT (3/4/6,5K)
20W 2000lm 120° IP66 LITE

Example application