

LED line LITE


Code: 203488

EAN: 5905378203488

LED line LITE Floodlight PHOTON 20W  
4000K 2000lm with motion sensor



LITE PHOTON LED line indicator with 20W and 4000K light colour is an advanced lighting solution providing a light stream of 2000 lm. It displays high light efficiency of 100 lm/W and long-lasting service life, reaching L70B50 for approximately 30,000 hours. Equipped with motion sensor and dusk sensor, it automatically activates when the presence is detected.



Technical data

| Parameter                                                              | Value                  |
|------------------------------------------------------------------------|------------------------|
| Energy efficiency class 2019/2015                                      | F                      |
| Warranty                                                               | 3                      |
| Power                                                                  | • 20 W                 |
| Voltage                                                                | • 220-240 V AC         |
| Correlated colour temperature                                          | • 4000 K               |
| Colour of the light                                                    | White                  |
| Colour rendering index Ra                                              | 80                     |
| IK protection rating                                                   | 05                     |
| IEC protection class                                                   | I                      |
| Luminous efficacy                                                      | 100                    |
| Luminous flux                                                          | 2000                   |
| The lumen maintenance factor                                           | 96                     |
| Lifetime L70B50                                                        | 30 000 h               |
| Survival factor                                                        | 0.9                    |
| Colour consistency in McAdam ellipses                                  | ≤6                     |
| Wyniki tłumaczenia Functional description of the daylight sensor [LUX] | Min 5 lx - Max 2000 lx |
| Rated power                                                            | 220-240V AC            |
| Mounting type                                                          | surface                |

| Parameter                                  | Value              |
|--------------------------------------------|--------------------|
| Mounting height                            | 2.3-5.0m           |
| Frequency of the supply voltage            | 50/60Hz            |
| Beam angle                                 | 120                |
| Sensor type                                | PIR                |
| LED type                                   | SMD2835            |
| LED quantity                               | 28                 |
| Power Factor                               | 0,7                |
| Number of on/off cycles                    | 18000              |
| Lamp's warm-up time to 60%                 | 1                  |
| Ambient temperature suitable for operation | -20÷40             |
| Length                                     | 120                |
| Width                                      | 62                 |
| Height                                     | 153                |
| Weight                                     | 251                |
| Colour                                     | Black              |
| Material (housing)                         | Die cast aluminium |
| Material (cover)                           | Tempered glass     |


LED line LITE

Code: 203488


EAN: 5905378203488

LED line LITE Floodlight PHOTON 20W  
4000K 2000lm with motion sensor

Technical drawing




Light distribution



Additional product photos




Logistics data




Single packaging

|          |         |
|----------|---------|
| Quantity | 1       |
| Width    | 120 mm  |
| Height   | 153 mm  |
| Length   | 62 mm   |
| Weight   | 0,33 kg |



Bulk packaging

|          |          |
|----------|----------|
| Quantity | 20       |
| Width    | 347 mm   |
| Height   | 283 mm   |
| Length   | 380 mm   |
| Volume   | 0,037 m3 |
| Weight   | 6,95 kg  |



Europallet

|                   |        |
|-------------------|--------|
| Quantity          | 800    |
| Height            | 1,90 m |
| Quantity in layer | 160    |
| Number of layers  | 5      |
| Bulk quantity     | 40     |
| Weight            | 303 kg |

---

LED line LITE

Code: 203488

EAN: 5905378203488

**LED line LITE Floodlight PHOTON 20W  
4000K 2000lm with motion sensor**

---

**Example application**