

LED line PRIME

Code: 228542

EAN: 5905378228542

LED NANO T8 G13 fluorescent tube
4000K 18W 2700lm 230V 270° 120cm PC
PRIME



LED line Nano 150 lm/W is a breakthrough in energy-efficient lighting. With very high luminous efficacy, it provides exceptional brightness with minimal power consumption, allowing for maximum reduction in energy costs. Made from shatterproof material, it guarantees complete safety in workshops, warehouses, and schools. The **Flicker Free** standard (SVM < 0.01) eliminates flicker, protecting eyesight and ensuring the highest comfort of work. It is the perfect combination of durability, powerful light output, and care for users' health.



Technical data

Parameter	Value
Energy efficiency class 2019/2015	D
Warranty	5
Power	• 18 W
Voltage	• 185-265 V AC
Correlated colour temperature	• 4000 K
Colour of the light	White
Colour rendering index Ra	80
IP protection rating	IP20
Luminous efficacy	150
Luminous flux	2700
Lifetime L70B50	50 000 h

Parameter	Value
Frequency of the supply voltage	50/60Hz
Beam angle	270
Power Factor	0,5
Number of on/off cycles	50000
Ambient temperature suitable for operation	"-20 ~ 45
For indoor use	Inside
Length	1200 mm
Lamp's diameter	26 mm
Diameter	26 mm
Weight	0,06 kg
Material (housing)	Polycarbonate


LED line PRIME

Code: 228542

EAN: 5905378228542

LED NANO T8 G13 fluorescent tube
4000K 18W 2700lm 230V 270° 120cm PC
PRIME

Technical drawing




Light distribution

Additional product photos




Logistics data




Single packaging

Width	28 mm
Height	28 mm
Length	1220 mm
Weight	0,08 kg



Bulk packaging

Quantity	25
Width	175 mm
Height	175 mm
Length	1235 mm
Weight	3,0 kg



Europallet

Quantity	600
Height	1,3 m
Bulk quantity	24
Weight	100 kg

LED line PRIME

Code: 228542

EAN: 5905378228542

**LED NANO T8 G13 fluorescent tube
4000K 18W 2700lm 230V 270° 120cm PC
PRIME**

Example application

