

LED line LITE


Code: 203532

EAN: 5905378203532

LED line LITE Floodlight PHOTON 30W
4000K 3000lm with motion sensor



LITE PHOTON 30W 4000K LED line emitting a 3000 lm light stream is an advanced solution with high energy efficiency, achieving 100 lm/W light efficiency. Made of cast aluminium and tempered glass, it is characterized by exceptional durability and resistance to adverse weather conditions. Equipped with a motion sensor and adjustable lighting angle, it allows optimal space lighting.



Technical data

Parameter	Value
Energy efficiency class 2019/2015	E
Warranty	3
Power	• 30 W
Voltage	• 220-240 V AC
Correlated colour temperature	• 4000 K
Colour of the light	White
Colour rendering index Ra	80
IP protection rating	IP65
IK protection rating	05
IEC protection class	I
Luminous efficacy	100
Luminous flux	3000
The lumen maintenance factor	96
Lifetime L70B50	30 000 h
Survival factor	0.9
Colour consistency in McAdam ellipses	≤6
Wyniki tłumaczenia Functional description of the daylight sensor [LUX]	Min 5 lx - Max 2000 lx
Rated power	220-240V AC

Parameter	Value
Mounting type	surface
Mounting height	2.3-5.0m
Frequency of the supply voltage	50/60Hz
Beam angle	120
Sensor type	PIR
LED type	SMD2835
LED quantity	45
Power Factor	0,9
Number of on/off cycles	18000
Lamp's warm-up time to 60%	1
Ambient temperature suitable for operation	-20÷40
Length	139
Width	63
Height	173
Weight	360
Colour	Black
Material (housing)	Die cast aluminium
Material (cover)	Tempered glass

LED line LITE


Code: 203532

EAN: 5905378203532

LED line LITE Floodlight PHOTON 30W

4000K 3000lm with motion sensor

Technical drawing



Light distribution




SYNOPSIS

Additional product photos




Logistics data




Single packaging

Quantity	1
Width	139 mm
Height	173 mm
Length	63 mm
Weight	0,44 kg



Bulk packaging

Quantity	12
Width	329 mm
Height	200 mm
Length	470 mm
Volume	0,030 m3
Weight	5,63 kg



Europallet

Quantity	480
Height	1,8 m
Quantity in layer	96
Number of layers	5
Bulk quantity	40
Weight	250 kg

LED line LITE

Code: 203532

EAN: 5905378203532

**LED line LITE Floodlight PHOTON 30W
4000K 3000lm with motion sensor**

Example application