

LED line LITE


Code: 200906

EAN: 5905378200906

Downlight MOLLY 24W 2550lm 4000K square LITE



Downlight LED MOLLY 24W from LED line LITE is a perfect solution for demanding users. It is characterized by a light stream of 2550 lm and a colour temperature of 4000 K, providing natural color reproduction thanks to the Ra >80 factor. IP20 leak class guarantees adequate indoor protection.




Technical data

Parameter	Value
Energy efficiency class 2019/2015	D
Warranty	3
Power	• 24 W
Voltage	• 170-260 V AC
Correlated colour temperature	• 4000 K
Colour of the light	White
Colour rendering index Ra	80
IP protection rating	IP20
IEC protection class	II
Luminous efficacy	105
Luminous flux	2550
The lumen maintenance factor	96
Lifetime L70B50	30 000 h
Survival factor	0.9
Colour consistency in McAdam ellipses	≤6


Parameter	Value
Frequency of the supply voltage	50/60Hz
LED type	SMD LED 2835
LED quantity	144
Power Factor	0,5
Number of on/off cycles	20000
Ambient temperature suitable for operation	-20÷40
For indoor use	Inside
Mounting hole diameter	190-210
Length	220
Width	220
Height	26
Weight	273.4
Colour	White
Material (housing)	Polycarbonate

Downlight MOLLY 24W 2550lm 4000K square LITE

Technical drawing




Light distribution



Additional product photos




Logistics data




Single packaging

Width	220 mm
Height	26 mm
Length	220 mm
Weight	0,37 kg



Bulk packaging

Quantity	40
Width	450 mm
Height	80 mm
Length	420 mm
Volume	0,015 m3
Weight	15,15 kg



Europallet

Height	1920 mm
Quantity in layer	80
Number of layers	24
Bulk quantity	1920
Weight	727,2 kg

LED line LITE

Code: 200906

EAN: 5905378200906

**Downlight MOLLY 24W 2550lm 4000K
square LITE**

Example application

