LED line PRIME   Code: 470607   EAN: 5907777470607

LED line Ceiling light round 220-240V 22W LUNAR MV

LED LUNAR from LED line PRIME is a 22W round plaphone, offering high light efficiency of 85 lm/W and a light stream of 1870 lm. It is characterized by a temperature of 4,000 K light, which provides natural and pleasant lighting. Thanks to IP65 leak class and polycarbonate material, the lamp is resistant to atmospheric factors.

CE

Technical data

Parameter	Value
Energy efficiency class 2019/2015	E
Energy class	A+
Warranty	5
Power	• 22 W
Voltage	• 220-240 V AC
Correlated colour temperature	• 4000 K
Colour of the light	White
Colour rendering index Ra	80
IP protection rating	IP65
IK protection rating	10
IEC protection class	II
Luminous efficacy	85
Luminous flux	1870
The lumen maintenance factor	96
Lifetime L70B50	50 000 h
Survival factor	0.9
Colour consistency in McAdam ellipses	≤6

Parameter	Value
Output current	0,101
Hold time	10s / 30s / 90s / 3min / 6min / 12min
Stand-by dimming level	20%
Frequency of the supply voltage	50/60Hz
Fixture's diameter	300
Beam angle	120
Sensor type	Microwave
LED type	SMD2835
LED quantity	200
Lifespan	50 000 h
Number of on/off cycles	50000
Lamp's warm-up time to 60%	1
Ambient temperature suitable for operation	-40÷45
Height	40
Colour	White
Material (housing)	Polycarbonate
Material (cover)	Polycarbonate

LED line PRIME   Code: 470607   EAN: 5907777470607

## LED line Ceiling light round 220-240V 22W LUNAR MV

Technical drawing

Light distribution

C0 - C180   C90 - C270   [cd/klm]

Additional product photos

Logistics data

Single packaging

Quantity	1
Width	305 mm
Height	50 mm
Length	305 mm
Weight	1,17 kg

Bulk packaging

Quantity	10
Width	320 mm
Height	320 mm
Length	525 mm
Volume	0,05 m3
Weight	11,7 kg
Comments	

Europallet

Quantity	200
Height	1744 mm
Quantity in layer	4
Number of layers	5
Bulk quantity	20
Weight	234 kg

LED line PRIME

Code: 470607

EAN: 5907777470607

LED line Ceiling light round 220-240V 22W LUNAR MV

Example application