

LED line PRIME


Code: 217676

EAN: 5905378217676

ESTADIO 250W 5000K 20° 170lm/w
CRI80 PRIME

New

The stadium ESTADIO 250W is a modern light source that is characterized by high light efficiency at 170 lm/W. Thanks to the colour of the light 5000K and the CRI80 colour reproduction factor, the setting provides excellent lighting quality. High IP66 leak class and IK10 resistance make it ideal for difficult external conditions.



Technical data

Parameter	Value
Warranty	5
Power	• 250 W
Voltage	• 100-227 V AC
Correlated colour temperature	• 5000 K
Colour of the light	White
IP protection rating	IP66
IK protection rating	10
IEC protection class	I
Luminous efficacy	170
Luminous flux	42500
The lumen maintenance factor	96
Lifetime L70B50	100 000 h
Colour consistency in McAdam ellipses	≤6
Frequency of the supply voltage	50/60Hz

Parameter	Value
CRI colour rendering index	80
Beam angle	20
LED type	EMC5050
LED quantity	100
Power Factor	0,95
Lamp's warm-up time to 60%	0,5 s
Ambient temperature suitable for operation	-40 / +45
For indoor use	Outside
Length	388
Width	305
Height	150
Weight	4500
Material (housing)	Aluminium
Material (cover)	polycarbonate

LED line PRIME


Code: 217676

EAN: 5905378217676

ESTADIO 250W 5000K 20° 170lm/w
CRI80 PRIME

Technical drawing


Light distribution



Additional product photos




Logistics data




Single packaging

Weight	5 kg
--------	------



Bulk packaging

Quantity	5
Weight	



Europallet

LED line PRIME

Code: 217676

EAN: 5905378217676

**ESTADIO 250W 5000K 20° 170lm/w
CRI80 PRIME**

Example application