

LED line LITE

Code: 203389

EAN: 5905378203389

LED line LITE Floodlight LUMINO 50W
4000K 5000lm with motion sensor



LITE LITE 50W LED line light is a modern and effective light source with a luminous flux of 5,000 lumens at a colour temperature of 4000 K. Using SMD LED technology, it delivers performance of 100 lm/W. The construction in the form of aluminium casting and tempered glass guarantees durability and resistance to atmospheric conditions with IP44 class of leak and IK05 degree of protection.



Technical data

Parameter	Value
Energy efficiency class 2019/2015	F
Warranty	3
Power	• 50 W
Correlated colour temperature	• 4000 K
Colour of the light	White
Colour rendering index Ra	70
IP protection rating	IP44
IK protection rating	05
IEC protection class	I
Luminous efficacy	100
Luminous flux	5000
The lumen maintenance factor	96
Lifetime L70B50	25 000 h
Survival factor	0.9
Colour consistency in McAdam ellipses	≤6
Hold time	10s - 10min

Parameter	Value
Frequency of the supply voltage	50/60Hz
Beam angle	110
Sensor type	PIR
LED type	SMD LED
LED quantity	56
Power Factor	0,9
Lamp's warm-up time to 60%	1
Ambient temperature suitable for operation	-20÷40
For indoor use	Inside
Length	198
Width	183
Height	79
Weight	510
Material (housing)	Die cast aluminium
Material (cover)	Tempered glass


LED line LITE

Code: 203389


EAN: 5905378203389

LED line LITE Floodlight LUMINO 50W
4000K 5000lm with motion sensor


Technical drawing




Light distribution



Additional product photos




Logistics data




Single packaging

Quantity	1
Width	198 mm
Height	79 mm
Length	183 mm
Weight	0,49 kg



Bulk packaging

Quantity	20
Width	400 mm
Height	350 mm
Length	430 mm
Volume	0,060 m3
Weight	10,15 kg



Europallet

Height	1720 mm
Quantity in layer	120
Number of layers	4
Bulk quantity	480
Weight	243,6 kg

LED line LITE

Code: 203389

EAN: 5905378203389

**LED line LITE Floodlight LUMINO 50W
4000K 5000lm with motion sensor**

Example application