

LED line LITE

Code: 202870

EAN: 5905378202870

DOWNLIGHT EASY FIX PRO
3CCT(3K/4K/5K) 24W 2400lm square
IP20 White LITE



LED line LITE Downlight EASY FIX PRO 24W is an advanced lighting setting that offers a 2400 lm light stream at 24 W power. It allows smooth adjustment of the colour temperature in the range of 3000 K to 5000 K, allowing perfect adjustment of light to different needs. Thanks to its robust design and high quality materials, it provides E-class energy efficiency and long life to 25,000 hours.



Technical data

Parameter	Value
Energy efficiency class 2019/2015	E
Power	• 24 W
Voltage	• 220-240 V AC
Correlated colour temperature	• 3000 K • 4000 K • 5000 K
Colour of the light	White
Colour rendering index Ra	80
IP protection rating	IP20
IK protection rating	05
IEC protection class	II
Luminous efficacy	100
Luminous flux	2400
The lumen maintenance factor	96
Lifetime L70B50	25 000 h
Survival factor	0.9
Dimmable function	PWM
Colour consistency in McAdam ellipses	≤6

Parameter	Value
Frequency of the supply voltage	50/60Hz
Beam angle	110
LED type	SMD2835
LED quantity	224
Power Factor	0,7
Number of on/off cycles	20000
Lamp's warm-up time to 60%	1
Ambient temperature suitable for operation	-20÷40
For indoor use	Inside
Mounting hole diameter	60-250
Length	292
Width	292
Height	19,5
Weight	900
Colour	White
Material (cover)	Polycarbonate


LED line LITE

Code: 202870


EAN: 5905378202870

DOWNLIGHT EASY FIX PRO
3CCT(3K/4K/5K) 24W 2400lm square
IP20 White LITE

Technical drawing






Light distribution



Additional product photos



Logistics data



Single packaging

Quantity	1
Width	292 mm
Height	19,5 mm
Length	292 mm
Weight	0,7 kg

Bulk packaging

Quantity	10
Width	319 mm
Height	220 mm
Length	512 mm
Volume	0,035 m3
Weight	10,7 kg
Comments	

Europallet

Quantity	300
Height	1,8 m
Quantity in layer	100
Number of layers	3
Bulk quantity	30
Weight	346 kg

LED line LITE

Code: 202870

EAN: 5905378202870

**DOWNLIGHT EASY FIX PRO
3CCT(3K/4K/5K) 24W 2400lm square
IP20 White LITE**

Example application