

LED line LITE Code: 245534 EAN: 5901583245534

## LED bulb G9 4000K 4W 350lm 230V 270° Ceramic LITE





LITE G9 4W 4000K LED line bulb is a modern light source with a power of 4 W that provides a light stream of 350 lm. It is characterized by a neutral colour of light 4000 K, ideal for various working spaces. With a light output of 88 lm/W and a light angle of 270°, it guarantees an effective scattering of light. Its durability reaches up to 30,000 hours, and the number of switching cycles is as much as 50,000.









#### **Technical data**

Parameter	Value
Energy efficiency class 2019/2015	F
Energy class	A+
Warranty	3
Power	• 4 W
Voltage	• 220-240 V AC
Correlated colour temperature	• 4000 K
Colour of the light	White
Colour rendering index Ra	80
Luminous efficacy	88
Luminous flux	350 lm
The lumen maintenance factor	96
Lifetime L70B50	30 000 h
Survival factor	0.9

Parameter	Value
Colour consistency in McAdam ellipses	≤6
Frequency of the supply voltage	50/60Hz
Fixture's diameter	16 mm
Beam angle	270 °
LED type	SMD2835
Power Factor	0,4
Number of on/off cycles	50000
Lamp's warm-up time to 60%	1
Ambient temperature suitable for operation	-20÷40
For indoor use	Inside
Height	49
Colour	white
Material (housing)	Ceramics




LED line LITE Code: 245534 EAN: 5901583245534

# LED bulb G9 4000K 4W 350lm 230V 270° Ceramic LITE

### **Technical drawing**



### **Light distribution**




### Additional product photos






## Logistics data






Quantity	1
Width	50 mm
Height	50 mm
Length	60 mm
Weight	0,01 kg



### **Bulk packaging**

Quantity	500
Width	610 mm
Height	235 mm
Length	150 mm
Volume	0,021 m3
Weight	7,455 kg
Comments	



#### Europallet

Quantity	40000
Height	1,6 m
Quantity in layer	3000
Number of layers	13
Bulk quantity	80
Weight	1120 kg

## MORE EFFICIENCY FOR THE LED WORLD



LED line LITE Code: 245534 EAN: 5901583245534

## LED bulb G9 4000K 4W 350lm 230V 270° Ceramic LITE

**Example application**