



LED line PRIME

Code: LL-35-12

EAN: 5907777479204

Power Supply 35-12 IP67 36W 12V PRIME

The PRIME 35-12 IP67 12V LED line power supply is an advanced power supply with 36 W output, which provides a stable voltage of 12 V. Thanks to the IP67 leak class, the device is resistant to water and dust, which guarantees reliability in difficult weather conditions. The input voltage range is 90 to 265 V AC at 47-63 Hz.



Technical data

Parameter	Value
Warranty	5
Power	• 36 W
Voltage	• 90-265 V AC
IEC protection class	II
Output current range	0 ÷ 3A
Input voltage frequency range	47 ÷ 63Hz
Rated current	3A
Safety standards	IP67
Efficiency	0,82

Parameter	Value
Voltage tolerance	-/+5.0%
Ambient humidity	20 ÷ 90%
Insulation strength	3kVAC
EMC standards	EN55015
Mounting type	surface
Inrush current (typ.)	70A/230VAC
Ambient temperature suitable for operation	-30÷50
Output voltage	• 12 V


LED line PRIME

Code: LL-35-12

EAN: 5907777479204

Power Supply 35-12 IP67 36W 12V PRIME

Technical drawing




Light distribution

Additional product photos




Logistics data




Single packaging

Quantity	1
Width	45 mm
Height	30 mm
Length	165 mm
Weight	0,24 kg



Bulk packaging

Quantity	50
Width	240 mm
Height	260 mm
Length	345 mm
Weight	16,8 kg



Europallet

Quantity	2880
Height	1060 mm
Bulk quantity	36
Weight	748 kg

LED line PRIME

Code: LL-35-12

EAN: 5907777479204

Power Supply 35-12 IP67 36W 12V PRIME

Example application