

LED line LITE

Code: 205604

EAN: 5905378205604

Panel Backlit 2in1 40W 4000K 4000LM
620x620 Black LITE



Backlit panel 2in1 40W 4000K 4000LM is a LED luminaire of exceptional quality, offering an energy-efficient light source with a light stream of 4000 lm. Color light 4000 K provides neutral, pleasant lighting. IP20 protection class and high durability (L70B50: 30,000 h) make it ideal for interiors.



Technical data

Parameter	Value
Energy efficiency class 2019/2015	E
Warranty	2
Power	• 40 W
Voltage	• 220-240 V AC
Correlated colour temperature	• 4000 K
Colour of the light	White
Colour rendering index Ra	80
IP protection rating	IP20
IK protection rating	02
IEC protection class	I
Luminous efficacy	100
Luminous flux	4000
The lumen maintenance factor	96

Parameter	Value
Lifetime L70B50	30 000 h
Survival factor	0.9
Dimmable function	PWM
Colour consistency in McAdam ellipses	≤6
Frequency of the supply voltage	50/60Hz
Beam angle	120
Power Factor	0.9
Lamp's warm-up time to 60%	1 s
Ambient temperature suitable for operation	-20÷40
For indoor use	Inside
Height	38
Material (housing)	Metal
Material (cover)	polystyrene

LED line LITE

Code: 205604

EAN: 5905378205604

Panel Backlit 2in1 40W 4000K 4000LM
620x620 Black LITE


Technical drawing

Light distribution

Additional product photos




Logistics data




Single packaging

Width	630 mm
Height	45 mm
Length	630 mm
Weight	1,67 kg



Bulk packaging

Quantity	6
Width	645 mm
Height	300 mm
Length	655 mm
Volume	0,128 m3
Weight	10,32 kg



Europallet

Height	1820 mm
Quantity in layer	24
Number of layers	2
Bulk quantity	48
Weight	82,56 kg

LED line LITE

Code: 205604

EAN: 5905378205604

**Panel Backlit 2in1 40W 4000K 4000LM
620x620 Black LITE**

Example application