

LED line PRIME

Code: 202726

EAN: 5905378202726

**FLOODLIGHT 3CCT (3K/4K/5K) 30W  
4200lm 120° IP66 PRIME**



The 30W PRIME Floodlight LED line is an advanced high-energy device with 4200 lumens with a light efficiency of 140 lm/W. Thanks to IP66 leak class and high resistance IK08, it is ideal for difficult external conditions. The aluminium housing ensures durability and effective heat removal. The angle of light distribution is 120° and the life of the diodes is estimated to be 50,000 hours.



**Technical data**

| Parameter  | Value                            |
|--|----------------------------------|
| Energy efficiency class 2019/2015  | D                                |
| Warranty   | 5/7*                             |
| Power  | • 30 W                           |
| Voltage  | • 100-277 V AC                   |
| Correlated colour temperature  | • 3000 K<br>• 4000 K<br>• 5000 K |
| Colour of the light  | CCT                              |
| Colour rendering index Ra  | 70                               |
| IP protection rating   | IP66                             |
| IK protection rating   | 08                               |
| IEC protection class   | I                                |
| Luminous efficacy  | 140                              |
| Luminous flux  | 4200                             |
| The lumen maintenance factor   | 96                               |
| Lifetime L70B50  | 50 000 h                         |
| L80B* – difference B10–B50 ≈ 1% (according to LightingEurope) – negligible | 35000 h                          |

| Parameter                                  | Value          |
|--|----------------|
| Survival factor                            | 0.9            |
| Colour consistency in McAdam ellipses      | ≤6             |
| Wire length                                | 890 mm         |
| Mounting type                              | surface        |
| Frequency of the supply voltage            | 50/60Hz        |
| Beam angle                                 | 120            |
| LED type                                   | SMD2835        |
| Number of on/off cycles                    | 50000          |
| Ambient temperature suitable for operation | -40÷45         |
| Length                                     | 252            |
| Width                                      | 213            |
| Height                                     | 43,5           |
| Weight                                     | 1              |
| Material (housing)                         | Aluminium      |
| Material (cover)                           | Tempered glass |

LED line PRIME

Code: 202726


EAN: 5905378202726

**FLOODLIGHT 3CCT (3K/4K/5K) 30W  
4200lm 120° IP66 PRIME**


**Technical drawing**





**Light distribution**



**Additional product photos**



**Logistics data**



**Single packaging**

|        |         |
|--------|---------|
| Width  | 252 mm  |
| Height | 43,5 mm |
| Length | 213 mm  |
| Weight | 1 kg    |

**Bulk packaging**

|          |          |
|----------|----------|
| Quantity | 10       |
| Width    | 480 mm   |
| Height   | 285 mm   |
| Length   | 320 mm   |
| Volume   | 0,043 m3 |
| Weight   | 10,35 kg |
| Comments |          |

**Europallet**

|                   |          |
|-------------------|----------|
| Quantity          | 200      |
| Height            | 1710 mm  |
| Quantity in layer | 40       |
| Number of layers  | 6        |
| Bulk quantity     | 240      |
| Weight            | 248,4 kg |

---

LED line PRIME

Code: 202726

EAN: 5905378202726

**FLOODLIGHT 3CCT (3K/4K/5K) 30W  
4200lm 120° IP66 PRIME**

---

**Example application**