

LED line PRIME

Code: 205833

EAN: 5905378205833

LED line PRIME Panel Backlit 34W
4000K 4760lm UGR<19 595x595



The PRIME LED line panel is an advanced 34W lighting luminaire, generating an impressive light stream of 4760 lm. It is characterized by the colour of 4000K light and highly effective SMD LEDs 2835, which provides a illumination with a capacity of 140 lm/W. Ugr<19 guarantees low glare, and a solid aluminium and polystyrene housing ensures durability. The product has a long life of L70B50 at level 70.



Technical data

Parameter	Value
Energy efficiency class 2019/2015	D
Warranty	5
Power	• 34 W
Voltage	• 200-240 V AC
Correlated colour temperature	• 4000 K
Colour of the light	White
Colour rendering index Ra	80
IP protection rating	IP20
IK protection rating	02
IEC protection class	II
Luminous efficacy	140
Luminous flux	4760
The lumen maintenance factor	96
Lifetime L70B50	50 000 h
Survival factor	0.9

Parameter	Value
Dimmable function	PWM
Colour consistency in McAdam ellipses	≤6
Frequency of the supply voltage	50/60Hz
Beam angle	90
LED type	SMD LED 2835
LED quantity	72
Power Factor	0,9
Number of on/off cycles	50000
Lamp's warm-up time to 60%	1 s
Ambient temperature suitable for operation	-20÷40
For indoor use	Inside
Height	28
Colour	white
Material (housing)	Aluminium
Material (cover)	polystyrene

LED line PRIME

Code: 205833

EAN: 5905378205833

LED line PRIME Panel Backlit 34W
4000K 4760lm UGR<19 595x595




Technical drawing

Light distribution

Additional product photos



Logistics data



Single packaging

Quantity	1
Width	30 mm
Height	640 mm
Length	600 mm
Weight	1,53 kg

Bulk packaging

Quantity	5
Width	170 mm
Height	655 mm
Length	615 mm
Volume	0,075 m3
Weight	10,4 kg
Comments	

Europallet

Height	1880 mm
Quantity in layer	25
Number of layers	2
Bulk quantity	60
Weight	132 kg

LED line PRIME

Code: 205833

EAN: 5905378205833

**LED line PRIME Panel Backlit 34W
4000K 4760lm UGR<19 595x595**

Example application

