

LED line PRIME

Code: 210639

EAN: 5905378210639

**Connector I linear for 3 phase track
LUMICANTO black with feeding PRIME**

The LUMICANTO bus connector in black with PRIME power supply is a functional solution characterized by a solid design. A product with a length of 163 mm, a width of 33 mm and a height of 32 mm, made of durable plastic. Powered by 220-240V AC voltage and 16A rated current, it provides high reliability. Thanks to the protection class I and IP20 degree, it will be perfect for interiors.



Technical data

Parameter	Value
Warranty	5/7*
IEC protection class	I
Rated power	220-240V AC
Rated current	16A
Mounting type	3 phase rail
Frequency of the supply voltage	50/60Hz
Ambient temperature suitable for operation	5÷40

Parameter	Value
Length	163
Width	33
Height	32
Power supply connection	tak
Equivalent	XTS 14
Colour	Black
Material (housing)	Plastic

LED line PRIME

Code: 210639

EAN: 5905378210639

**Connector I linear for 3 phase track
LUMICANTO black with feeding PRIME**



Technical drawing

Light distribution

Additional product photos



Logistics data



Single packaging

Width	170 mm
Height	30 mm
Length	30 mm
Weight	0,1 kg

Bulk packaging

Quantity	100
Width	250 mm
Height	220 mm
Length	400 mm
Volume	0,022 m ³
Weight	10,4 kg

Europallet

Height	1760 mm
Quantity in layer	900
Number of layers	8
Bulk quantity	7200
Weight	367,2 kg

LED line PRIME

Code: 210639

EAN: 5905378210639

**Connector I linear for 3 phase track
LUMICANTO black with feeding PRIME**

Example application