

LED line LITE

Code: 203495

EAN: 5905378203495

**Floodlight PHOTON 4000K 10W 1000lm
120° IP65 LITE**



LITE PHOTON 10W 4000K 1000lm LED line is an advanced lighting solution. It is characterized by a light stream of 1000 lm and a light efficiency of 100 lm/W, which ensures high energy efficiency. Made of cast aluminium and equipped with tempered glass, it is resistant to different atmospheric conditions (IP65 leak class) and mechanical (IK06 protection level).



Technical data

Parameter	Value
Energy efficiency class 2019/2015	E
Warranty	3
Power	• 10 W
Voltage	• 220-240 V AC
Correlated colour temperature	• 4000 K
Colour of the light	White
Colour rendering index Ra	80
IP protection rating	IP65
IK protection rating	05
IEC protection class	I
Luminous efficacy	100
Luminous flux	1000
The lumen maintenance factor	96
Lifetime L70B50	30 000 h
Survival factor	0.9
Colour consistency in McAdam ellipses	≤6
Rated power	220-240V AC

Parameter	Value
Mounting type	surface
Frequency of the supply voltage	50/60Hz
Beam angle	120
LED type	SMD2835
LED quantity	15
Power Factor	0,7
Number of on/off cycles	18000
Lamp's warm-up time to 60%	1
Ambient temperature suitable for operation	-20÷40
Length	110 mm
Width	115 mm
Height	32 mm
Weight	0,19 kg
Colour	Black
Material (housing)	Die cast aluminium
Material (cover)	Tempered glass


LED line LITE

Code: 203495


EAN: 5905378203495

**Floodlight PHOTON 4000K 10W 1000lm
120° IP65 LITE**

Technical drawing



Light distribution



Additional product photos



Logistics data



Single packaging

Quantity	1
Width	105 mm
Height	118 mm
Length	30 mm
Weight	0,22 kg

Bulk packaging

Quantity	30
Width	263 mm
Height	220 mm
Length	362 mm
Volume	
Weight	6,95 kg

Europallet

Quantity	1800
Height	1,9 mm
Quantity in layer	
Number of layers	
Bulk quantity	60
Weight	500 kg

LED line LITE

Code: 203495

EAN: 5905378203495

**Floodlight PHOTON 4000K 10W 1000lm
120° IP65 LITE**

Example application