

LED line LITE

Code: 477620

EAN: 5907777477620

**Hermetic luminaire TRI-PROOF 4000K
70W 8400lm IP65 150cm gray LITE**



The TRI-PROOF LED line LITE housing with a power of 70W and a length of 1550 mm is an advanced lighting solution, characterized by durability and high efficiency. It emits a pleasant white light with a colour temperature of 4000K and a light stream of 8400 lumens. IP65 leak class and mechanical resistance IK08 provide reliability in difficult conditions.



Technical data

Parameter	Value
Energy efficiency class 2019/2015	E
Warranty	3
Power	• 70 W
Voltage	• 185-265 V AC
Correlated colour temperature	• 4000 K
Colour of the light	White
Colour rendering index Ra	80
IP protection rating	IP65
IK protection rating	08
IEC protection class	II
Luminous efficacy	120
Luminous flux	8400
The lumen maintenance factor	96
Lifetime L70B50	35 000 h
Survival factor	0.9
Colour consistency in McAdam ellipses	≤6
Standby power	0
Mounting type	surface

Parameter	Value
Frequency of the supply voltage	50/60Hz
CRI colour rendering index	80
Beam angle	120
LED type	2835
LED quantity	192
Lifespan	35 000 h
Power Factor	0,9
Number of on/off cycles	20000
Lamp's warm-up time to 60%	1
Ambient temperature suitable for operation	-20÷40
Length	1550 mm
Width	82 mm
Height	55 mm
Weight	0,68 kg
Colour	White
Material (housing)	Polycarbonate
Material (cover)	Polycarbonate


LED line LITE

Code: 477620


EAN: 5907777477620

**Hermetic luminaire TRI-PROOF 4000K
70W 8400lm IP65 150cm gray LITE**

Technical drawing



Light distribution



Additional product photos



Logistics data



Single packaging

Quantity	1
Width	1550 mm
Height	48 mm
Length	82 mm
Weight	0,8 kg

Bulk packaging

Quantity	10
Width	270 mm
Height	190 mm
Length	1560 mm
Volume	0,080 m3
Weight	11,35 kg
Comments	

Europallet

Quantity	160
Height	1,70 m
Quantity in layer	160
Number of layers	1
Bulk quantity	16
Weight	207 kg

LED line LITE

Code: 477620

EAN: 5907777477620

**Hermetic luminaire TRI-PROOF 4000K
70W 8400lm IP65 150cm gray LITE**

Example application