

LED line PRIME


Code: 216792

EAN: 5905378216792

LED line PRIME Road luminaire CAMINO  
50W 4000K 7000lm



CAMINO 70W road mounting from LED line PRIME is an advanced solution with light performance of 9800 lm. It is characterized by a colour temperature of 4000 K, which provides natural, white light. Made of aluminium and tempered glass, it achieves a high level of protection IP66 and IK08, guaranteeing resistance to atmospheric conditions and mechanical damage. It works in voltage range 220-240 V AC.



Technical data

Parameter	Value
Energy efficiency class 2019/2015	C
Warranty	5
Power	• 70 W
Voltage	• 220-240 V AC
Correlated colour temperature	• 4000 K
Colour of the light	White
Colour rendering index Ra	70
IP protection rating	IP66
IK protection rating	08
IEC protection class	I
Luminous efficacy	140
Luminous flux	9800 lm
The lumen maintenance factor	96
Lifetime L70B50	100 000 h
Survival factor	0.9

Parameter	Value
Colour consistency in McAdam ellipses	≤6
ULOR	0 %
Frequency of the supply voltage	50/60Hz
Beam angle	150 x 110
LED type	LUMILEDS 2835
LED quantity	96
Power Factor	0,9
Lamp's warm-up time to 60%	1
Ambient temperature suitable for operation	-40÷50
Length	514
Width	200
Height	80
Material (housing)	Die cast aluminium
Material (cover)	Tempered glass

LED line PRIME


Code: 216792

EAN: 5905378216792

LED line PRIME Road luminaire CAMINO  
50W 4000K 7000lm

Technical drawing




Light distribution



Additional product photos



Logistics data



Single packaging

Width	514 mm
Height	80 mm
Length	200 mm
Weight	2,3 kg

Bulk packaging

Quantity	1
Width	5600 mm
Height	1160 mm
Length	2360 mm
Volume	15,33 m3
Weight	

Europallet

Height	1840 mm
Number of layers	1
Bulk quantity	96
Weight	330,4 kg

LED line PRIME

Code: 216792

EAN: 5905378216792

**LED line PRIME Road luminaire CAMINO  
50W 4000K 7000lm**

**Example application**

