

LED line LITE Code: 209947 EAN: 5905378209947

LED line LITE Downlight EASY FLEX 9-12-15W CCT 1120lm round white





New

Downlight EASY FLEX 9-12-15W CCT 1120Im is a modern round LED line LITE lighting product. Its high light efficiency is 1120 lumens at power expenditure 9, 12 or 15 W, which provides excellent lighting conditions. Thanks to the possibility to choose the temperature of the colour of light (3000 K, 4000 K, 5000 K) and the universal assembly (mountain, surface and suspended), DOWNLIGHT fits perfectly into various interior arrangements.

















Technical data

Parameter	Value
Energy efficiency class 2019/2015	E
Warranty	3
Power	• 9 W • 12 W • 15 W
Voltage	• 220-240 V AC
Correlated colour temperature	• 3000 K • 4000 K • 5000 K
Colour rendering index Ra	80
IP protection rating	IP20
IK protection rating	05
IEC protection class	II
Luminous efficacy	75
Luminous flux	1120
The lumen maintenance factor	96
Lifetime L70B50	30 000 h
Survival factor	0.9

Parameter	Value
Colour consistency in McAdam ellipses	≤6
Frequency of the supply voltage	50/60Hz
Fixture's diameter	170
Beam angle	120
LED type	SMD2835
LED quantity	84
Number of on/off cycles	15000
Lamp's warm-up time to 60%	1s
Ambient temperature suitable for operation	`-20 ÷ 40
Installation method	3in1 surface mounted, flush mounted, suspended
Mounting hole diameter	65-130
Height	17
Weight	0,24 kg
Colour	White




LED line LITE Code: 209947 EAN: 5905378209947

LED line LITE Downlight EASY FLEX 9-12-15W CCT 1120lm round white

Technical drawing

Light distribution

Luminous [cd/klm]



Additional product photos













Logistics data









Single packaging

Width	31 mm
Height	175 mm
Length	175 mm
Weight	0,215 kg

Bulk packaging

Quantity	40
Width	365 mm
Height	335 mm
Length	370 mm
Weight	13,08 kg

Europallet

Bulk quantity 960

MORE EFFICIENCY FOR THE LED WORLD



LED line LITE Code: 209947 EAN: 5905378209947

LED line LITE Downlight EASY FLEX 9-12-15W CCT 1120lm round white

Example application