

LED line PRIME Code: 201156 EAN: 5905378201156

LED line PRIME Ceiling lamp ACTON 18W 1900lm 3000K IP54 square





ACTON 18W LED Plafon is a modern lighting setting with high light efficiency of 1900 Im and 3000 K colour temperature, providing pleasant, warm light. It is characterized by IP54 leak class and IK08 resistance, making it ideal for use under difficult conditions. The reliability of the product is underlined by the five-year guarantee. Polycarbonate housing guarantees durability and aesthetics.

















Darameter

Technical data

Parameter	Value
Energy efficiency class 2019/2015	F
Warranty	5
Power	• 18 W
Voltage	• 220-240 V AC
Correlated colour temperature	• 3000 K
Colour of the light	White
Colour rendering index Ra	80
IP protection rating	IP54
IK protection rating	08
IEC protection class	II
Luminous efficacy	105
Luminous flux	1900
The lumen maintenance factor	96
Lifetime L70B50	30 000 h
Survival factor	0.9

Parameter	value
Dimmable function	PWM
Colour consistency in McAdam ellipses	≤6
Frequency of the supply voltage	50/60Hz
Fixture's diameter	220
Beam angle	120
LED type	SMD2835
Power Factor	0,9
Lamp's warm-up time to 60%	1
Ambient temperature suitable for operation	-25÷40
Height	51
Weight	620
Colour	White
Material (housing)	Polycarbonate
Material (cover)	Polycarbonate


مبياد/\




LED line PRIME Code: 201156 EAN: 5905378201156

LED line PRIME Ceiling lamp ACTON 18W 1900lm 3000K IP54 square

Technical drawing



Light distribution




Additional product photos









Logistics data







Single packaging

Width	220 mm	
Height	220 mm	
Length	60 mm	
Weight	0,72 kg	

Bulk packaging

Quantity	20
Width	470 mm
Height	250 mm
Length	615 mm
Volume	0,072 m3
Weight	14,75 kg

Europallet

Quantity	400
Height	1750 mm
Quantity in layer	40
Number of layers	7
Bulk quantity	280
Weight	206,5 kg

MORE EFFICIENCY FOR THE LED WORLD



LED line PRIME Code: 201156 EAN: 5905378201156

LED line PRIME Ceiling lamp ACTON 18W 1900lm 3000K IP54 square

Example application