

LED line LITE

Code: 228900

EAN: 5905378228900



Floodlight PHOTON S 3CCT (3/4/6,5K)
10W 1000lm 120° IP66 LITE



New



PHOTON S is a professional floodlight for buildings, halls, and open areas. The aluminum housing, tempered glass, and pressure equalization system ensure IP66 and IK08. Efficient LEDs 100 lm/W, tool-free installation, 3 light colors, a lumen output of 1,000–30,000 lm, and a PIR option guarantee savings and versatile applications.



Technical data

Parameter	Value
Energy efficiency class 2019/2015	F
Warranty	3
Power	10 W
Voltage	185-265 V AC
Correlated colour temperature	3000 K 4000 K 6500 K
Colour of the light	CCT
Colour rendering index Ra	80
IP protection rating	IP66
IK protection rating	06
IEC protection class	I
Luminous efficacy	100
Luminous flux	1000

Parameter	Value
Lifetime L70B50	30 000 h
Frequency of the supply voltage	50/60Hz
Beam angle	120°
LED type	2835 18V
Power Factor	>=0,9
Ambient temperature suitable for operation	-20÷45
Length	118 mm
Width	74 mm
Height	27 mm
Weight	0,22 kg
Material (housing)	Aluminium

LED line LITE


Code: 228900

EAN: 5905378228900

Floodlight PHOTON S 3CCT (3/4/6,5K)

10W 1000lm 120° IP66 LITE


Technical drawing



Light distribution


Additional product photos

Logistics data




Single packaging

Width	105 mm
Height	35 mm
Length	145 mm
Weight	0,26kg



Bulk packaging

Quantity	20
Width	230 mm
Height	195 mm
Length	300 mm
Weight	5,2kg



Europallet

Quantity	2400
Height	1,8 m
Bulk quantity	120
Weight	660 kg

LED line LITE

Code: 228900

EAN: 5905378228900

Floodlight PHOTON S 3CCT (3/4/6,5K)
10W 1000lm 120° IP66 LITE

Example application