

LED line PRIME

Code: 479587-DALI

EAN: 5905378221543

**LINKER hermetic fixture 4000K 21W
3150lm IP65 60cm gray PRIME DALI**



The LINKER 21W fixture by LED line PRIME is an advanced lighting solution characterized by high luminous efficiency of 3150 lumens at an efficacy of 150 lm/W. It offers a light color of 4000K, which ensures natural color rendering ($Ra \geq 80$). The IP65 ingress protection class and IK08 impact resistance enhance its durability in harsh conditions.



Technical data

Parameter	Value
Energy efficiency class 2019/2015	D
Warranty	5
Power	• 21 W
Voltage	• 220-240 V AC
Correlated colour temperature	• 4000 K
Colour of the light	White
Colour rendering index Ra	80
IP protection rating	IP65
IK protection rating	08
IEC protection class	I
Luminous efficacy	150
Luminous flux	3150
The lumen maintenance factor	96
Lifetime L70B50	100 000 h
L80B* – difference B10–B50 \approx 1% (according to LightingEurope) – negligible	75000 h
L90B* – difference B10–B50 \approx 1% (according to LightingEurope) – negligible	50000 h
Dimmable function	Dali

Parameter	Value
Frequency of the supply voltage	50/60Hz
Beam angle	120
LED type	SMD2837
Lifespan	100 000 h
Power Factor	0,95
Number of on/off cycles	50000
Lamp's warm-up time to 60%	1
Ambient temperature suitable for operation	-25 ÷ 45
Length	600 mm
Width	72 mm
Height	61 mm
Weight	1,9 kg
Colour	Grey
Material (housing)	Polycarbonate
Material (cover)	Polycarbonate
DALI	• YES


LED line PRIME

Code: 479587-DALI

EAN: 5905378221543

**LINKER hermetic fixture 4000K 21W
3150lm IP65 60cm gray PRIME DALI**

Technical drawing




Light distribution

Additional product photos



Logistics data



Single packaging

Quantity	1
Width	75 mm
Height	65 mm
Length	630 mm
Weight	1,04 kg

Bulk packaging

Quantity	20
Width	355 mm
Height	323 mm
Length	648 mm
Volume	
Weight	28 kg

Europallet

Quantity	240
Height	1500 mm
Quantity in layer	
Number of layers	
Bulk quantity	12
Weight	361 kg

LED line PRIME

Code: 479587-DALI

EAN: 5905378221543

**LINKER hermetic fixture 4000K 21W
3150lm IP65 60cm gray PRIME DALI**

Example application