

LED line PRIME

Code: 204089

EAN: 5905378204089

LED line PRIME FUSION linear lamp
20W 4000K 2600lm 0-10V LR40° white



FUSION LED line PRIME 20W 4000K is an innovative lighting that provides high-performance light performance at 130 lm/W. Thanks to a total luminous flux of 2600 lm, the setting perfectly illuminates various spaces. The use of LR40° lenses allows for precise adjustment of the angle of falling light. IP20 leak class and IK08 resistance guarantee durability under different conditions of use.



Technical data

Parameter	Value
Energy efficiency class 2019/2015	C
Warranty	5
Power	• 20 W
Voltage	• 220-240 V AC
Correlated colour temperature	• 4000 K
Colour of the light	White
Colour rendering index Ra	80
IP protection rating	IP20
IK protection rating	08
IEC protection class	I
Luminous efficacy	130
Luminous flux	2600
The lumen maintenance factor	96
Lifetime L70B50	50 000 h

Parameter	Value
Survival factor	0.9
Dimmable function	0-10
Colour consistency in McAdam ellipses	≤6
Sling length	200 cm
Standby power	0
Mounting type	mixed
Frequency of the supply voltage	50/60Hz
Power Factor	0,9
Lamp's warm-up time to 60%	1 s
Ambient temperature suitable for operation	-20÷45
For indoor use	Inside
Length	586
Width	70
Height	52

LED line PRIME

Code: 204089

EAN: 5905378204089


LED line PRIME FUSION linear lamp
20W 4000K 2600lm 0-10V LR40° white

Technical drawing

Light distribution


Additional product photos

Logistics data




Single packaging

Width	586 mm
Height	52 mm
Length	70 mm
Weight	1,14 kg



Bulk packaging

Quantity	12
Width	690 mm
Height	260 mm
Length	260 mm
Volume	0,046 m3
Weight	13,93 kg
Comments	



Europallet

Quantity	288
Height	1710 mm
Quantity in layer	48
Number of layers	6
Bulk quantity	288
Weight	672 kg

LED line PRIME

Code: 204089

EAN: 5905378204089

**LED line PRIME FUSION linear lamp
20W 4000K 2600lm 0-10V LR40° white**

Example application