

LED line LITE Code: 240133 EAN: 5901583240133

LED strip 150/5m SMD 12V YELLOW 2,4W IP65 8mm 5m LITE

LED line 150 SMD 12V in yellow with a power of 2.4 In this efficient lighting solution. It is characterized by effective SMD3528 diodes, offering long-term operation and low energy consumption. Thanks to a wide light angle of 120°, the tape ensures uniform light scattering. The stability of the assembly guarantees high quality 3M adhesive and flexible white laminate.





Technical data

Parameter	Value
Warranty	3
Power	• 2.4 W / m
Voltage	• 12 V DC
Colour of the light	Yellow
IEC protection class	III
Cutting section	10 cm
The lumen maintenance factor	>0,7
Lifetime L70B50	30 000 h
Dimmable function	PWM
Current (1m)	0,2
Beam angle	120
LED type	SMD3528
Compatible dimmer type	PWM

Parameter	Value
Laminate (colour)	White
Laminate (thickness)	2
LED quantity (1m)	30
Type of adhesive tape	3M 300 LSE
Lifespan	100 000 h
Number of on/off cycles	50000
Lamp's warm-up time to 60%	1
Ambient temperature suitable for operation	-20÷45
Length	5000 mm
Width	8
Height	3
Weight	0,152 kg




LED line LITE Code: 240133 EAN: 5901583240133

LED strip 150/5m SMD 12V YELLOW 2,4W IP65 8mm 5m LITE


Technical drawing

Light distribution



Additional product photos


Logistics data






Single packaging

Quantity	5 m
Width	180 mm
Height	20 mm
Length	180 mm
Weight	0,167 kg



Bulk packaging

Quantity	40
Width	320 mm
Height	180 mm
Length	360 mm
Volume	0,020 m3
Weight	6,76 kg
Comments	



Europallet

Quantity	12000 m
Height	1800 mm
Quantity in layer	240
Number of layers	10
Bulk quantity	2400

MORE EFFICIENCY FOR THE LED WORLD



LED line LITE Code: 240133 EAN: 5901583240133

LED strip 150/5m SMD 12V YELLOW 2,4W IP65 8mm 5m LITE

Example application