

LED line PRIME

Code: 219281

EAN: 5905378219281

PHANTOM 200W 4000K 175lm/W
35000lm 1-10V 60° CRI80 MV PRIME



Phantom PRIME is a high-performance high-bay luminaire that combines energy efficiency, reliability, and ease of installation. Designed with warehouses, sports facilities, and food or pharmaceutical plants in mind, it ensures excellent working conditions and quick return on investment.

Key features:

- Power: 70 W / 100 W / 150 W / 200 W, efficiency up to 190 lm/W (CRI 70) or 175 lm/W (CRI 80)
- Adjustable beam angles: 60° / 90° / 120° for precise illumination
- PZH certificate – approved for environments with strict hygiene requirements
- Smart dimming (1-10 V) with Merrytek sensors or via DALI2
- IP65 & IK08 protection, operating temperature from -30 °C to +45 °C
- Lightweight aluminum housing – quick and safe high-level installation
- 5-year warranty – full service support



Technical data

Parameter	Value
Energy efficiency class 2019/2015	B
Warranty	5
Power	<ul style="list-style-type: none">• 200 W
Voltage	<ul style="list-style-type: none">• 100-277 V AC
Correlated colour temperature	<ul style="list-style-type: none">• 4000 K
Colour of the light	White
Colour rendering index Ra	80
IP protection rating	IP65
IK protection rating	08
IEC protection class	I
Luminous efficacy	175
Luminous flux	35000
The lumen maintenance factor	96
Lifetime L70B50	100 000 h

Parameter	Value
Dimmable function	1-10
Colour consistency in McAdam ellipses	6
Frequency of the supply voltage	50/60Hz
Fixture's diameter	330 mm
Beam angle	60
Sensor type	Microwave
LED type	SMD 2835
LED quantity	640
Power Factor	0,95
Number of on/off cycles	50000
Lamp's warm-up time to 60%	1 s
Ambient temperature suitable for operation	-30÷45
Height	156 mm
Material (housing)	Aluminium


LED line PRIME

Code: 219281


EAN: 5905378219281

PHANTOM 200W 4000K 175lm/W
35000lm 1-10V 60° CRI80 MV PRIME



Technical drawing






Light distribution



Additional product photos



Logistics data



Single packaging

Quantity	1
Width	380 mm
Height	380 mm
Length	170 mm
Weight	2,4 kg

Bulk packaging

Quantity	1
Width	380 mm
Height	170 mm
Length	380 mm
Volume	0,024 m3
Weight	2,4 kg

Europallet

Quantity	66
Height	1870 mm
Quantity in layer	6
Number of layers	11
Bulk quantity	66
Weight	25 kg

LED line PRIME

Code: 219281

EAN: 5905378219281

**PHANTOM 200W 4000K 175lm/W
35000lm 1-10V 60° CRI80 MV PRIME**

Example application

