

LED line PRIME

Code: 479983

EAN: 5907777479983

LED strip 720/5m SMD 24V 2700K 6,5W
IP20 10mm 5m 1300lm/m PRIME



144 SMD 24V 2700K 6,5W 200lm/W LED line PRIME is a modern and energy-efficient light source, characterized by a warm light colour with a temperature of 2700K. Light performance is as high as 200 lm/W, providing intense lighting with low energy consumption. The product is equipped with a dimming function, which allows to adjust brightness to individual needs.



Technical data

Parameter	Value	Parameter	Value
Energy efficiency class 2019/2015	B	Luminous flux (lm)	1300
Warranty	5	Current (Im)	0,27
Power	• 6.5 W / m	Beam angle	120
Voltage	• 24 V DC	LED type	SMD
Correlated colour temperature	• 2700 K	LED quantity	720
Colour of the light	White	Compatible dimmer type	PWM
Colour rendering index Ra	80	Laminate (colour)	White
IP protection rating	IP20	Laminate (thickness)	3
IEC protection class	III	LED quantity (lm)	144
Cutting section	6,25 cm	Type of adhesive tape	3M 300 LSE
Luminous efficacy	200	Ambient temperature suitable for operation	-25÷45
The lumen maintenance factor	96	For indoor use	Inside
Lifetime L70B50	50 000 h	Length	5000
Survival factor	0.9	Width	10
Dimmable function	PWM	Height	2,5
Colour consistency in McAdam ellipses	≤3	Weight	0,115 kg
Wire length	200 mm		


LED line PRIME

Code: 479983


EAN: 5907777479983

LED strip 720/5m SMD 24V 2700K 6,5W
IP20 10mm 5m 1300lm/m PRIME

Technical drawing






Light distribution



Additional product photos

Logistics data



Single packaging

Quantity	5 m
Width	153 mm
Height	15 mm
Length	153 mm
Weight	0,131 kg
Comments	

Bulk packaging

Quantity	40
Width	320 mm
Height	180 mm
Length	360 mm
Volume	0,020 m3
Weight	5,4 kg
Comments	

Europallet

Quantity	12000 m
Height	1800 mm
Quantity in layer	240
Number of layers	10
Bulk quantity	2400
Weight	300 kg

LED line PRIME

Code: 479983

EAN: 5907777479983

**LED strip 720/5m SMD 24V 2700K 6,5W
IP20 10mm 5m 1300lm/m PRIME**

Example application