

LED line LITE

Code: 201002

EAN: 5905378201002

Downlight MOLLY 24W 2550lm CCT 3000-6000K round LITE



The round Downlight LED MOLLY 24W from LED line LITE is a modern minimalist design, ideal for a variety of interiors. With an impressive light stream of 2550 lumens and the possibility of adjusting the colour temperature in the range of 3000-6000K, it provides excellent colour reproduction with Ra>80. IP20 leak class provides dust protection and practical design allows installation in plaster or plaster systems.




Technical data

Parameter	Value
Energy efficiency class 2019/2015	D
Warranty	3
Power	• 24 W
Voltage	• 170-260 V AC
Correlated colour temperature	• 3000 K • 4000 K • 6000 K
Colour of the light	White
Colour rendering index Ra	80
IP protection rating	IP20
IEC protection class	II
Luminous efficacy	105
Luminous flux	2550
The lumen maintenance factor	96
Lifetime L70B50	30 000 h
Survival factor	0.9
Colour consistency in McAdam ellipses	≤6


Parameter	Value
Frequency of the supply voltage	50/60Hz
Fixture's diameter	220 mm
Beam angle	110
LED type	SMD LED 2835
LED quantity	240
Power Factor	0.5
Number of on/off cycles	20000
Ambient temperature suitable for operation	-20÷40
For indoor use	Inside
Mounting hole diameter	190-210
Height	26
Weight	188
Colour	White
Material (housing)	Polycarbonate

Downlight MOLLY 24W 2550lm CCT
3000-6000K round LITE

Technical drawing




Light distribution



Additional product photos




Logistics data




Single packaging

Width	226 mm
Height	34 mm
Length	224 mm
Weight	0,2 kg



Bulk packaging

Quantity	40
Width	472 mm
Height	390 mm
Length	672 mm
Volume	0,123 m3
Weight	12,3 kg



Europallet

Height	1888 mm
Quantity in layer	120
Number of layers	4
Bulk quantity	480
Weight	147,6 kg

LED line LITE

Code: 201002

EAN: 5905378201002

**Downlight MOLLY 24W 2550lm CCT
3000-6000K round LITE**

Example application

