


LED line LITE

Code: 209848

EAN: 5905378209848

Park Luminaire PARKLITE 50W CCT 6000lm grey LITE

PARKLITE 50W CCT Park luminaire offers exceptional power of 50 W and a light stream of 6000 lm, which provides excellent lighting performance. Its construction materials, including aluminium and tempered glass, guarantee high resistance to damage (IK08) and effective protection against atmospheric conditions (IP65). The lamp is characterized by high energy efficiency with a power factor PF 0.9.



Technical data

Parameter	Value
Warranty	3
Power	• 50 W
Voltage	• 220-240 V AC
Correlated colour temperature	• 3000 K • 4000 K • 6000 K
Colour rendering index Ra	80
IK protection rating	08
IEC protection class	I
Luminous efficacy	120
Luminous flux	6000
The lumen maintenance factor	96
Lifetime L70B50	25 000 h
Survival factor	0.9
Dimmable function	PWM
Colour consistency in McAdam ellipses	≤6

Parameter	Value
ULOR	2,3 %
Wire length	400 mm
Frequency of the supply voltage	50/60Hz
Beam angle	100
LED type	SMD LED 2835
LED quantity	384
Power Factor	0,9
Lamp's warm-up time to 60%	1 s
Ambient temperature suitable for operation	-30°C ~ +50°C
Height	117
Weight	2190
Material (housing)	Aluminium
Material (cover)	tempered glass

LED line LITE


Code: 209848

EAN: 5905378209848


Park Luminaire PARKLITE 50W CCT
6000lm grey LITE

Technical drawing




Light distribution



Additional product photos



Logistics data



Single packaging

Width	420 mm
Height	118 mm
Length	425 mm
Weight	2,25 kg

Bulk packaging

Quantity	4
Width	550 mm
Height	445 mm
Length	40 mm
Volume	0,009 m3
Weight	9,3 kg

Europallet

Height	1780 mm
Quantity in layer	8
Number of layers	4
Bulk quantity	32
Weight	99,4 kg

LED line LITE

Code: 209848

EAN: 5905378209848

**Park Luminaire PARKLITE 50W CCT
6000lm grey LITE**

Example application