

LED line PRIME

Code: LL-60-12

EAN: 5905378200159

Power Supply 60-12 IP67 60W 12V
PRIME

The PRIME 60-12 IP67 LED line power supply is an advanced 60W output power device designed to operate in difficult conditions. It offers an output voltage of 12V at a stable nominal current of up to 5A. Thanks to IP67, it effectively protects against water and dust, which ensures reliability in different environments. The product has a high efficiency of 84%, which translates into energy efficiency.



5
WARRANTY

IP
67

PF
0,95

12V
DC

Technical data

Parameter	Value	Parameter	Value
Warranty	5	Insulation strength	3kVAC
Power	• 60 W	EMC standards	EN55015
Voltage	• 90-264 V AC	Mounting type	surface
IEC protection class	II	Inrush current (typ.)	70A/230VAC
Output current range	0 ÷ 5A	Power Factor	>=0,95
Input voltage frequency range	50 ÷ 60Hz	Ambient temperature suitable for operation	-30÷40
Rated current	0,275	Length	166 mm
Safety standards	IP67	Width	42 mm
Efficiency	0,84	Height	33 mm
Voltage tolerance	-/+5.0%	Weight	0,4 kg
Ambient humidity	20 ÷ 90%	Output voltage	• 12 V


LED line PRIME

Code: LL-60-12

EAN: 5905378200159

Power Supply 60-12 IP67 60W 12V
PRIME

Technical drawing






Light distribution

Additional product photos



Logistics data



Single packaging

Quantity	1
Width	52 mm
Height	35 mm
Length	185 mm
Weight	0,42 kg

Bulk packaging

Quantity	40
Width	205 mm
Height	215 mm
Length	385 mm
Weight	17,3 kg

Europallet

Quantity	2400
Height	1,90 m
Quantity in layer	
Number of layers	
Bulk quantity	60
Weight	1100 kg

LED line PRIME

Code: LL-60-12

EAN: 5905378200159

Power Supply 60-12 IP67 60W 12V
PRIME

Example application