

LED line PRIME Code: 203457 EAN: 5905378203457

LED line PRIME Panel Backlit 42W 4000K 6300lm UGR<19 595x595

















Technical data

Parameter	Value
Energy efficiency class 2019/2015	В
Warranty	5
Power	• 42 W
Voltage	• 220-240 V AC
Correlated colour temperature	• 4000 K
Colour of the light	White
Colour rendering index Ra	80
IP protection rating	IP20
IK protection rating	02
IEC protection class	II
Luminous efficacy	150
Luminous flux	6300
The lumen maintenance factor	96
Lifetime L70B50	50 000 h
Survival factor	0.9

Parameter	Value
Dimmable function	PWM
Colour consistency in McAdam ellipses	≤6
Frequency of the supply voltage	50/60Hz
Beam angle	90
LED type	SMD LED 2835
LED quantity	108
Power Factor	0,9
Number of on/off cycles	25000
Lamp's warm-up time to 60%	1s
Ambient temperature suitable for operation	-25÷45
For indoor use	Inside
Height	28
Colour	White
Material (housing)	Aluminium
Material (cover)	polystyrene

The PRIME Backlit LED line panel with 42W power and 6300 Im




LED line PRIME Code: 203457 EAN: 5905378203457

LED line PRIME Panel Backlit 42W 4000K 6300lm UGR<19 595x595


Technical drawing

Light distribution

Luminous [cd/klm]



Additional product photos











Logistics data







Single packaging

Quantity	1
Width	645 mm
Height	30 mm
Length	605 mm
Weight	1,68 kg

Bulk packaging

Quantity	5
Width	630 mm
Height	180 mm
Length	670 mm
Volume	0,075 m3
Weight	10,4 kg
Comments	

Europallet

Height	1340 mm
Quantity in layer	30
Number of layers	2
Bulk quantity	60
Weight	124,8 kg

MORE EFFICIENCY FOR THE LED WORLD



LED line PRIME Code: 203457 EAN: 5905378203457

LED line PRIME Panel Backlit 42W 4000K 6300lm UGR<19 595x595

Example application