

LED line LITE Code: 202269 EAN: 5905378202269

## LED bulb E27 2700K 7W 840lm 230V 360° FILAMENT A60 DIM Glass LITE





LED bulb E27 7W 2700K 840lm FILAMENT A60 from LED line LITE is a modern light source with a power of 7 W, which emits warm, white light at a light stream of as many as 840 lumens. Thanks to philament technology, we get the effect of a classic bulb, eliminating flickering simultaneously. The life of 25,000 hours and the 360° lighting angle provide effective and even interior lighting.











#### **Technical data**

Parameter	Value
Energy efficiency class 2019/2015	E
Warranty	3
Power	• 7 W
Voltage	• 220-240 V AC
Correlated colour temperature	• 2700 K
Colour of the light	White
Colour rendering index Ra	80
IP protection rating	IP20
Luminous efficacy	120
Luminous flux	840 lm
The lumen maintenance factor	96
Lifetime L70B50	25 000 h
Survival factor	0.9
Dimmable function	PWM
Colour consistency in McAdam ellipses	≤6
Frequency of the supply voltage	50/60Hz

Parameter	Value
Lamp's type	A60
Fixture's diameter	60 mm
Beam angle	360 °
LED type	Filament
LED quantity	4
Lifespan	25 000 h
Number of on/off cycles	50000
Lamp's warm-up time to 60%	1
Ambient temperature suitable for operation	-20÷40
For indoor use	Inside
Height	108
Weight	32
Material	Glass
Material (housing)	Glass
Material (cover)	glass



LED line LITE Code: 202269 EAN: 5905378202269

# LED bulb E27 2700K 7W 840lm 230V 360° FILAMENT A60 DIM Glass LITE

### **Technical drawing**

#### **Light distribution**




#### Additional product photos






### Logistics data






Quantity	1
Width	50 mm
Height	59 mm
Length	50 mm
Weight	0,03 kg



Bulk packaging

Quantity	50
Width	325 mm
Height	240 mm
Length	325 mm
Volume	0,025 m3
Weight	2.78 ka



#### Europallet

Height	1920 mm
Quantity in layer	300
Number of layers	8
Bulk quantity	2400
Weight	133,44 kg



LED line LITE Code: 202269 EAN: 5905378202269

# LED bulb E27 2700K 7W 840lm 230V 360° FILAMENT A60 DIM Glass LITE

### **Example application**

